



RAAML

OMG RISK ANALYSIS
AND ASSESSMENT
MODELING LANGUAGE

Risk Analysis and Assessment Modeling Language (RAAML) Libraries and Profiles

Version 1.1 Beta 2

OMG Document Number: formal/22-12-06 [smc/22-12-03]

Standard document URL: <http://www.omg.org/spec/RAAML/>

Date: ~~March 2021~~

Deleted: December 2022

Deleted: 0

Copyright © 2021, Dassault Systemes

Copyright © 2021, Ford Motor Company

Copyright © 2021, Gesellschaft für Systems Engineering

Copyright © 2022, Object Management Group, Inc.

USE OF SPECIFICATION - TERMS, CONDITIONS & NOTICES

The material in this document details an Object Management Group specification in accordance with the terms, conditions and notices set forth below. This document does not represent a commitment to implement any portion of this specification in any company's products. The information contained in this document is subject to change without notice.

LICENSES

The companies listed above have granted to the Object Management Group, Inc. (OMG) a nonexclusive, royalty-free, paid up, worldwide license to copy and distribute this document and to modify this document and distribute copies of the modified version. Each of the copyright holders listed above has agreed that no person shall be deemed to have infringed the copyright in the included material of any such copyright holder by reason of having used the specification set forth herein or having conformed any computer software to the specification.

Subject to all of the terms and conditions below, the owners of the copyright in this specification hereby grant you a fully-paid up, non-exclusive, nontransferable, perpetual, worldwide license (without the right to sublicense), to use this specification to create and distribute software and special purpose specifications that are based upon this specification, and to use, copy, and distribute this specification as provided under the Copyright Act; provided that: (1) both the copyright notice identified above and this permission notice appear on any copies of this specification; (2) the use of the specifications is for informational purposes and will not be copied or posted on any network computer or broadcast in any media and will not be otherwise resold or transferred for commercial purposes; and (3) no modifications are made to this specification. This limited permission automatically terminates without notice if you breach any of these terms or conditions. Upon termination, you will destroy immediately any copies of the specifications in your possession or control.

PATENTS

The attention of adopters is directed to the possibility that compliance with or adoption of OMG specifications may require use of an invention covered by patent rights. OMG shall not be responsible for identifying patents for which a license may be required by any OMG specification, or for conducting legal inquiries into the legal validity or scope of those patents that are brought to its attention. OMG specifications are prospective and advisory only. Prospective users are responsible for protecting themselves against liability for infringement of patents.

GENERAL USE RESTRICTIONS

Any unauthorized use of this specification may violate copyright laws, trademark laws, and communications regulations and statutes. This document contains information which is protected by copyright. All Rights Reserved. No part of this work covered by copyright herein may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without permission of the copyright owner.

DISCLAIMER OF WARRANTY

WHILE THIS PUBLICATION IS BELIEVED TO BE ACCURATE, IT IS PROVIDED "AS IS" AND MAY CONTAIN ERRORS OR MISPRINTS. THE OBJECT MANAGEMENT GROUP AND THE COMPANIES LISTED ABOVE MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS PUBLICATION, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF TITLE OR OWNERSHIP, IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE. IN NO EVENT SHALL THE OBJECT MANAGEMENT GROUP OR ANY OF THE COMPANIES LISTED ABOVE BE LIABLE FOR ERRORS CONTAINED HEREIN OR FOR DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL, RELIANCE OR COVER DAMAGES, INCLUDING LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY ANY USER OR ANY THIRD PARTY IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS MATERIAL, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

The entire risk as to the quality and performance of software developed using this specification is borne by you. This disclaimer of warranty constitutes an essential part of the license granted to you to use this specification.

RESTRICTED RIGHTS LEGEND

Use, duplication or disclosure by the U.S. Government is subject to the restrictions set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software Clause at DFARS 252.227-7013 or in subparagraph (c)(1) and (2) of the Commercial Computer Software - Restricted Rights clauses at 48 C.F.R. 52.227-19 or as specified in 48 C.F.R. 227-7202-2 of the DoD F.A.R. Supplement and its successors, or as specified in 48 C.F.R. 12.212 of the Federal Acquisition Regulations and its successors, as applicable. The specification copyright owners are as indicated above and may be contacted through the Object Management Group, 9C Medway Road, PMB 274, Milford, MA 01757, U.S.A.

TRADEMARKS

CORBA®, CORBA logos®, FIBO®, Financial Industry Business Ontology®, FINANCIAL INSTRUMENT GLOBAL IDENTIFIER®, IIOP®, IMM®, Model Driven Architecture®, MDA®, Object Management Group®, OMG®, OMG Logo®, SoaML®, SOAML®, SysML®, UAF®, Unified Modeling Language®, UML®, UML Cube Logo®, VSIPL®, and XMI® are registered trademarks of the Object Management Group, Inc.

For a complete list of trademarks, see: http://www.omg.org/legal/tm_list.htm. All other products or company names mentioned are used for identification purposes only, and may be trademarks of their respective owners.

COMPLIANCE

The copyright holders listed above acknowledge that the Object Management Group (acting itself or through its designees) is and shall at all times be the sole entity that may authorize developers, suppliers and sellers of computer software to use certification marks, trademarks or other special designations to indicate compliance with these materials.

Software developed under the terms of this license may claim compliance or conformance with this specification if and only if the software compliance is of a nature fully matching the applicable compliance points as stated in the specification. Software developed only partially matching the applicable compliance points may claim only that the software was based on this specification, but may not claim compliance or conformance with this specification. In the event that testing suites are implemented or approved by Object Management Group, Inc., software developed using this specification may claim compliance or conformance with the specification only if the software satisfactorily completes the testing suites.

Table of Contents

PREFACE	1
1. SCOPE	4
1.1 INTRODUCTION	4
1.2 RAAML BACKGROUND.....	4
1.3 INTENDED USAGE	4
1.4 RELATED DOCUMENTS.....	5
2. CONFORMANCE	7
3. REFERENCES.....	8
3.1 NORMATIVE REFERENCES.....	8
3.2 OMG DOCUMENTS (NORMATIVE REFERENCES)	8
3.3 OTHER NORMATIVE REFERENCES	8
3.4 INFORMATIVE REFERENCES	8
4. ACKNOWLEDGEMENTS.....	9
5. TERMS AND DEFINITIONS.....	10
6. ACRONYMS AND ABBREVIATIONS	11
7. ADDITIONAL INFORMATION (NON-NORMATIVE)	12
7.1 LANGUAGE ARCHITECTURE	12
7.2 PHILOSOPHY	12
7.3 PRINCIPLES OF CREATING, EDITING, AND DISPLAYING OF COMPOSITE SITUATIONS IN DIAGRAMMATIC AND TABULAR VIEWS	12
7.3.1 Diagrammatic Situation Specification	13
7.3.2 Tabular Situation Specification.....	15
8. DIAGRAM LEGEND (NON-NORMATIVE)	18
9. RISK ANALYSIS AND ASSESSMENT MODELING LANGUAGE (RAAML) LIBRARY AND PROFILE 20	
9.1 CORE.....	20
9.1.1 Core::Core Library.....	21
9.1.2 Core::Core Profile.....	23
9.2 GENERAL	25
9.2.1 General::General Concepts Library	26
9.2.2 General::General Concepts Profile	37
9.3 METHODS::FMEA	48
9.3.1 Methods::FMEA::FMEALibrary	48
9.3.2 Methods::FMEA::FMEAProfile.....	52
9.4 METHODS::FTA	53
9.4.1 Methods::FTA::FTALibrary	53
9.4.2 Methods::FTA::FTAProfile.....	65
9.5 METHODS::STPA.....	78
9.5.1 Methods::STPA::STPA Library.....	78
9.5.2 Methods::STPA::STPA Profile.....	88
9.6 GSN.....	91
9.6.1 GSN::GSN Profile	92
9.7 METHODS::ISO 26262	99
9.7.1 Methods::ISO 26262::ISO 26262 Library	99
9.7.2 Methods::ISO 26262::ISO 26262 Profile	113

10. VIEWS 163

10.1 CORE 163

10.1.1 Core::Core Library 163

10.1.2 Core::Core Profile 163

10.2 GENERAL 164

10.2.1 General::General Concepts Library 164

10.2.2 General::General Concepts Profile 164

10.3 METHODS::FMEA 167

10.3.1 Methods::FMEA::FMEA Library 167

10.3.2 Methods::FMEA::FMEA Profile 168

10.4 METHODS::FTA 168

10.4.1 Methods::FTA::FTALibrary 168

10.4.2 Methods::FTA::FTAProfile 170

10.5 METHODS::STPA 171

10.5.1 Methods::STPA::STPA Library 171

10.5.2 Methods::STPA::STPA Profile 173

10.6 GSN 174

10.6.1 GSN::GSN Profile 174

10.7 METHODS::ISO 26262 176

10.7.1 Methods::ISO 26262::ISO 26262 Library 176

10.7.2 Methods::ISO 26262::ISO 26262 Profile 177

Table of Figures

Figure 7.1 – Fundamental situation modeling principles.....	13
Figure 7.2 – Typical Automotive Situation definition in the ISO26262 Library.....	14
Figure 7.3 – User Model Defining Operational Situation “Highway Driving Straight at Speed”	15
Figure 7.4 – HazardousEvent Definition in the ISO26262 Library.....	16
Figure 8.1 – Legend of color codes	18
Figure 8.2 – An example of using a legend	18
Figure 9.1 – Core concepts domain model	20
Figure 9.2 - AnySituation	22
Figure 9.3 - Causality	22
Figure 9.4 - Situation	23
Figure 9.5 - RelevantTo.....	23
Figure 9.6 - ControllingMeasure	24
Figure 9.7 - Violates	25
Figure 9.8 - IDCarrier.....	25
Figure 9.9 - AbstractEvent.....	26
Figure 9.10 - AbstractCause	27
Figure 9.11 - Cause.....	27
Figure 9.12 - DysfunctionalEvent.....	28
Figure 9.13 - AbstractFailureMode	28
Figure 9.14 - FailureMode.....	29
Figure 9.15 - AbstractEffect	30
Figure 9.16 - Effect.....	30
Figure 9.17 - Activation.....	31
Figure 9.18 - ErrorPropagation.....	32
Figure 9.19 - ErrorRealization.....	32
Figure 9.20 - HarmPotential	33
Figure 9.21 - Hazard.....	33
Figure 9.22 - Scenario	34
Figure 9.23 - AbstractRisk.....	34
Figure 9.24 - UndesiredState	35
Figure 9.25 - FailureMode.....	37
Figure 9.26 - Error	37
Figure 9.27 - Fault	38
Figure 9.28 - Detection	38
Figure 9.29 - Prevention	39
Figure 9.30 - Mitigation.....	39
Figure 9.31 - Recommendation	40
Figure 9.32 - FailureState	40
Figure 9.33 - AbstractFMEAItem.....	48
Figure 9.34 - FMEAItem	49
Figure 9.35 - LossOfFunction.....	50
Figure 9.36 - DegradationOfFunction	51
Figure 9.37 - IntermittentFunction	51
Figure 9.38 - PartialFunction	51
Figure 9.39 - UnintendedFunction.....	52
Figure 9.40 - ExceedingFunction.....	52
Figure 9.41 - DelayedFunction	52
Figure 9.42 - FMEAItem	53
Figure 9.43 - FTAElement.....	54
Figure 9.44 - FTATree.....	54
Figure 9.45 - Event	55
Figure 9.46 - BasicEvent	55

Figure 9.47 - IntermediateEvent	56
Figure 9.48 - TopEvent.....	56
Figure 9.49 - ConditionalEvent	57
Figure 9.50 - DormantEvent.....	57
Figure 9.51 - UndevelopedEvent.....	57
Figure 9.52 - HouseEvent.....	58
Figure 9.53 - ZeroEvent.....	58
Figure 9.54 - Gate.....	59
Figure 9.55 - AND.....	59
Figure 9.56 - OR.....	60
Figure 9.57 - NOT	60
Figure 9.58 - XOR.....	61
Figure 9.59 - SEQ.....	61
Figure 9.60 - INHIBIT.....	62
Figure 9.61 - MAJORITY_VOTE.....	62
Figure 9.62 - Tree.....	66
Figure 9.63 - Gate.....	66
Figure 9.64 - Event	66
Figure 9.65 - DormantEvent.....	67
Figure 9.66 - BasicEvent	68
Figure 9.67 - ConditionalEvent	69
Figure 9.68 - ZeroEvent.....	69
Figure 9.69 - HouseEvent.....	70
Figure 9.70 - AND.....	71
Figure 9.71 - OR.....	72
Figure 9.72 - SEQ.....	72
Figure 9.73 - XOR.....	73
Figure 9.74 - INHIBIT.....	74
Figure 9.75 - MAJORITY_VOTE.....	75
Figure 9.76 - NOT	75
Figure 9.77 - IntermediateEvent	76
Figure 9.78 - TopEvent.....	77
Figure 9.79 - TransferIn.....	77
Figure 9.80 - TransferOut	78
Figure 9.81 - OutOfSequence	79
Figure 9.82 - Late	79
Figure 9.83 - Early	79
Figure 9.84 - TooLong.....	80
Figure 9.85 - TooShort	80
Figure 9.86 - Provided	80
Figure 9.87 - NotProvided	81
Figure 9.88 - LossScenario	81
Figure 9.89 - InadequateControllerDecisions.....	83
Figure 9.90 - InadequateControlExecution.....	83
Figure 9.91 - InadequateProcessBehavior	83
Figure 9.92 - InadequateFeedbackAndInputs.....	84
Figure 9.93 - UnsafeControlAction	85
Figure 9.94 - Loss.....	85
Figure 9.95 - RiskRealization	86
Figure 9.96 - ControlAction	88
Figure 9.97 - Feedback	88
Figure 9.98 - UnsafeControlAction	89
Figure 9.99 - ControlledProcess	89
Figure 9.100 - Actuator	90
Figure 9.101 - Sensor.....	90
Figure 9.102 - Controller	90

Deleted: 0

Figure 9.103 - ControlStructure	91
Figure 9.104 - LossScenario	91
Figure 9.105 - Standard UML notation for stereotyped elements (from UML 2.5.1, Figure 12.25)	92
Figure 9.106 - Strategy notation	92
Figure 9.107 - Combined notation	92
Figure 9.108 - GSNNode	93
Figure 9.109 - GSNArgumentNode	93
Figure 9.110 - Solution	94
Figure 9.111 - Goal	94
Figure 9.112 - Strategy	95
Figure 9.113 - ContextualInformation	95
Figure 9.114 - ContextStatement	95
Figure 9.115 - Assumption	96
Figure 9.116 - Justification	96
Figure 9.117 - InContextOf	97
Figure 9.118 - SupportedBy	98
Figure 9.119 - TrafficAndPeople	99
Figure 9.120 - VehicleUsage	99
Figure 9.121 - RoadCondition	100
Figure 9.122 - Location	100
Figure 9.123 - EnvironmentalCondition	101
Figure 9.124 - OperationalCondition	101
Figure 9.125 - AbstractOperationalSituation	102
Figure 9.126 - TypicalAutomotiveSituation	102
Figure 9.127 - Exposure	103
Figure 9.128 - Severity	103
Figure 9.129 - ASIL	104
Figure 9.130 - Controllability	104
Figure 9.131 - Less	105
Figure 9.132 - More	105
Figure 9.133 - No	105
Figure 9.134 - Intermittent	106
Figure 9.135 - Unintended	106
Figure 9.136 - Early	107
Figure 9.137 - Late	107
Figure 9.138 - Inverted	107
Figure 9.139 - HazardousEvent	108
Figure 9.140 - AnyMalfunction	109
Figure 9.141 - AutomotiveEffect	109
Figure 9.142 - ISO26262SafetyRequirementTemplate	110
Figure 9.143 - AccidentScenario	110
Figure 9.144 - AnyTrafficAndPeople	111
Figure 9.145 - AnyVehicleUse	111
Figure 9.146 - AnyRoadCondition	112
Figure 9.147 - AnyLocation	112
Figure 9.148 - AnyEnvironmentalCondition	112
Figure 9.149 - SystemLevelEffect	113
Figure 9.150 - VehicleLevelEffect	113
Figure 9.151 - OperationalSituation	114
Figure 9.152 - MalfunctioningBehavior	114
Figure 9.153 - IndependenceRequirement	115
Figure 9.154 - ASILDecompose	115
Figure 9.155 - SafeState	116
Figure 9.156 - UserInfoRequirement	116
Figure 9.157 - RecoveryRequirement	116

Figure 9.158 - OperatingMode	117
Figure 9.159 - FunctionalSafetyRequirement.....	117
Figure 9.160 - SoftwareSafetyRequirement	118
Figure 9.161 - HardwareSafetyRequirement	118
Figure 9.162 - TechnicalSafetyRequirement	119
Figure 9.163 - SafetyGoal.....	119
Figure 9.164 - DependabilityRequirement	119
Figure 9.165 - Verified	120
Figure 9.166 - Confirmed	120
Figure 9.167 - HazardAndRiskAssessment.....	121
Figure 9.168 - LessonLearned	121
Figure 9.169 - ASILAssignment.....	121
Figure 9.170 - ASILOverrideRationale	122
Figure 10.1 - Core Library	163
Figure 10.2 - CoreProfile.....	163
Figure 10.3 - General Concepts Library.....	164
Figure 10.4 - General Concepts Profile	165
Figure 10.5 - FMEA Library	167
Figure 10.6 - FMEA Profile.....	168
Figure 10.7 - Events.....	169
Figure 10.8 - FTA Library	169
Figure 10.9 - FTA Profile.....	170
Figure 10.10 - STPA Library.....	173
Figure 10.11 - STPA Profile.....	174
Figure 10.12 - GSN Profile.....	175
Figure 10.13 - ISO 26262 Library	176
Figure 10.14 - All-Encompassing Operational Situations	177
Figure 10.15 - RequirementManagement	178
Figure 10.16 - ISO 26262 Profile	179

Deleted: 0

TABLE OF TABLES

Table 1.1 – Table of Related Documents 5

Table 5.1 – Description of terms and definitions used in this specification 10

Table 6.1 – Description of acronyms used in this specification 11

Table 7.1 – Table for Specifying Operational Situations with Situation “Highway Driving Straight at Speed” Defined 15

Table 7.2 – Hazardous Event Table with Grouped Columns..... 17

Table 9.1 – Mapping of core concepts to the SysML/UML language..... 21

Preface

OMG

Founded in 1989, the Object Management Group, Inc. (OMG) is an open membership, not-for-profit computer industry standards consortium that produces and maintains computer industry specifications for interoperable, portable and reusable enterprise applications in distributed, heterogeneous environments. Membership includes Information Technology vendors, end users, government agencies and academia. OMG member companies write, adopt, and maintain its specifications following a mature, open process. OMG's specifications implement the Model Driven Architecture® (MDA®), maximizing ROI through a full-lifecycle approach to enterprise integration that covers multiple operating systems, programming languages, middleware and networking infrastructures, and software development environments. OMG's specifications include: UML® (Unified Modeling Language™); CORBA® (Common Object Request Broker Architecture); CWM™ (Common Warehouse Metamodel); and industry-specific standards for dozens of vertical markets. More information on the OMG is available at <https://www.omg.org/>.

OMG Specifications

As noted, OMG specifications address middleware, modeling, and vertical domain frameworks. All OMG Specifications are available from this URL: <https://www.omg.org/spec>.

Specifications are organized by the following categories:

Domain Categories

Platform Categories

Other Categories

All of OMG's formal specifications may be downloaded without charge from our website. (Products implementing OMG specifications are available from individual suppliers.) Copies of specifications, available in PDF format, may be obtained from the Specifications Catalog cited above or by contacting the Object Management Group, Inc. at:

OMG Headquarters
92 Medway Road, PMB 274
Milford, MA 01757 USA
Tel: +1- 781-444-0404
Fax: +1-781-444-0320
Email: pubs@omg.org

Certain OMG specifications are also available as ISO standards. Please consult <https://www.iso.org>

Typographical Conventions

The type styles shown below are used in this document to distinguish programming statements from ordinary English. However, these conventions are not used in tables or section headings where no distinction is necessary.

Times/Times New Roman - 10 pt.: Standard body text

Helvetica/Arial - 10 pt. Bold: OMG Interface Definition Language (OMG IDL) and syntax elements.

Courier - 10 pt. Bold: Programming language elements.

Helvetica/Arial - 10 pt: Exceptions

Note – Terms that appear in *italics* are defined in the glossary. Italic text also represents the name of a document, specification, or other publication.

Issues

All OMG specifications are subject to continuous review and improvement. As part of this process, we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Documents, Report a Bug/Issue (<https://issues.omg.org/issues/create-new-issue>).

1. Scope

1.1 Introduction

There are two parts to this specification, one being normative and another informative. The normative part is:

- The Risk Analysis and Assessment Modeling Language (RAAML) Library and Profile (this document) defines concepts and relationships for capturing safety and reliability aspects of a system in the library and profile form.

The informative part is:

- The RAAML Example Model, Annex A (see document ad/2020-11-01), which illustrates practical usages of RAAML.

1.2 RAAML Background

Model-Based Systems Engineering (MBSE) is gaining popularity in organizations creating complex systems where it is crucial to collaborate in a multi-disciplinary environment. SysML, being one of the key MBSE components, has a good foundation for capturing requirements, architecture, constraints, views, and viewpoints. However, SysML does not provide the constructs to capture safety, reliability or security information in the system model. A group of industry experts at the OMG has been working since 2016 to define a new specification providing the necessary capabilities.

The need for a standardized UML profile/library for addressing safety, reliability and security aspects emerged long ago. Working group members have seen multiple commercial-grade model-based safety, reliability and security solution implementations being developed during the recent years and successfully used in practice. While the various safety, reliability and security implementations may fit the needs for a specific purpose, there are many instances where information needs to be traced and shared across multiple organizations. These inconsistent model-based solutions prohibit direct model sharing between organizations and across the various tools. One of the key goals for the working group is to reconcile these different approaches to alleviate the industry from repeatedly formulating safety, reliability and security constructs in their tools. The specification provides the modeling capabilities for tool vendors to build safety, reliability and security modeling tools that provide traditional representations (e.g., trees, tables, etc.) while using a modern model-based approach.

This RAAML 1.1 specification defines extensions to SysML needed to support safety, reliability and security analysis. It describes:

- the core concepts and shows how the simple concepts are powerful enough to unite all safety, reliability and security information across a variety of analysis methods
- the approach to automating several safety and reliability analyses, which is built on leveraging existing SysML functionalities to ensure that the profile and library is usable with existing tooling
- specific safety and reliability analysis methods and application domains that are supported
 - o Failure Mode and Effect Analysis (FMEA)
 - o Fault Tree Analysis (FTA)
 - o Systems Theoretic Process Analysis (STPA)
 - o Goal Structuring Notation (GSN)
 - o ISO 26262 Road Vehicles - Functional Safety
 - o Reliability Block Diagrams (RBD)
- extension mechanisms that are typically needed by the industry to apply the specification in practice

1.3 Intended Usage

The RAAML specification provides the foundation for conducting various safety and quality engineering activities including safety and reliability analysis methods. Besides the method support, linkages to the SysML model-of-interest

Deleted: and

Deleted: and

Deleted: and

Deleted: and

Deleted: and

Deleted: an

Deleted: d

Deleted: 0

Deleted: and

Deleted: and

Formatted: Font color: Text 1

Commented [AA1]: RAAML11-17

are provided, enabling integration with and traceability to the analyses. The specification can be used for modeling safety, reliability and security aspects directly in the model or as a standard language to import and export from external safety and reliability tools.

Deleted: and

The organization of RAAML facilitates tailoring the methodologies to specific engineering domains and industries to support the various assessment and certification agencies.

1.4 Related Documents

The specification is delivered as a set of related documents. The primary normative document is this document, while a set of additional machine-readable documents is provided to specify the UML profiles and model libraries, specified by this standard.

For each safety/reliability domain, supported by this standard (FMEA, FTA, ISO-26262, STPA and RBD) there is a pair of profile and library.

Deleted: and

In addition to that there is a pair of profile and library for the concepts used in multiple domains – General and General Security; and a pair of profile and library for the very core concepts that might be useful for the implementers of other standards in the safety/reliability/security domain.

GSN stands separately, as it is an add-on, which can be used with any of the aforementioned domains for additional substantiation of the safety models. It consists of just the profile; no library is necessary. The GSN profile only covers the GSN version 2 standard core notation.

Non-normative examples document is also provided, illustrating how to apply RAAML for capturing safety and reliability data.

Table 1.1 – Table of Related Documents

Document Number	Description	File Name	Nor-mative	Machine Readable
ptc/24-03-04	Core portion of the RAAML.	CoreRAAML.xmi	Y	Y
ptc/24-03-05	Library portion of the RAAML.	CoreRAAMLLib.xmi	Y	Y
ptc/24-03-06	General portion, shared across domains of the RAAML.	GeneralRAAML.xmi	Y	Y
ptc/24-03-07	General Library portion, shared across domains of the RAAML.	GeneralRAAMLLib.xmi	Y	Y
ptc/24-03-08	Goal Structuring Notation profile.	GSN.xmi	Y	Y
ptc/24-03-09	FMEA portion of the RAAML.	FMEA.xmi	Y	Y
ptc/24-03-10	FMEA Library portion of the RAAML.	FMEALib.xmi	Y	Y
ptc/24-03-11	FTA (Fault Tree Analysis) portion of the RAAML.	FTA.xmi	Y	Y
ptc/24-03-12	FTA (Fault Tree Analysis) Library portion of the RAAML.	FTALib.xmi	Y	Y
ptc/24-03-13	ISO26262 Functional Safety Standard portion of the RAAML	ISO26262.xmi	Y	Y
ptc/24-03-14	ISO26262 Functional Safety Standard Library portion of the RAAML	ISO26262Lib.xmi	Y	Y
ptc/24-03-15	STPA (Systems Theoretic Process Analysis) portion of the RAAML	STPA.xmi	Y	Y
ptc/24-03-16	STPA (Systems Theoretic Process Analysis) Library portion of the RAAML	STPALib.xmi	Y	Y
ptc/24-03-17	Security profile portion of the RAAML	GeneralRAAMLSecurity.xmi	Y	Y
ptc/24-03-18	Security library portion of the RAAML	GeneralRAAMLSecurityLib.xmi	Y	Y

Deleted: ptc/21-12-05

Deleted: ptc/21-12-06

Deleted: ptc/21-12-07

Deleted: ptc/21-12-08

Deleted: ptc/21-12-09

Deleted: ptc/21-12-10

Deleted: ptc/21-12-11

Deleted: ptc/21-12-12

Deleted: ptc/21-12-13

Deleted: ptc/21-12-14

Deleted: ptc/21-12-15

Deleted: ptc/21-12-16

Deleted: ptc/21-12-17

ptc/24-03-19	RBD (Reliability Block Diagram) profile portion of the RAAML	RBD.xmi	Y	Y
ptc/24-03-20	RBD (Reliability Block Diagram) library portion of the RAAML	RBDLib.xmi	Y	Y
ptc/24-03-21	MagicDraw model from which all XMIs and images were produced	Safety and Reliability Library and Profile.583.mdzip	N	Y
ptc/21-11-22	Risk Analysis and Assessment Modeling Language 1.1 Examples	OMG RAAML Examples 1.1.docx	N	N

Commented [AA2]: RAAML11-17

Deleted: 0

Deleted: 0

2. Conformance

RAAML specifies two types of conformance.

- Type 1 Conformance: RAAML model interchange conformance. A tool demonstrating model interchange conformance can import and export conformant XMI for all valid RAAML models.
- Type 2 Conformance: RAAML View specification conformance. A tool demonstrating view specification conformance shall implement the views specified in RAAML specification.

A tool vendor may choose to implement one method supported by the specification (FMEA, FTA, STPA, GSN, ~~ISO 26262 or RBD~~) and claim conformance to it.

Deleted: or

Commented [AA3]: RAAML11-17

3. References

3.1 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this specification. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply.

3.2 OMG Documents (Normative References)

- Unified Modeling Language (UML), 2.5.1, December 2017, <https://www.omg.org/spec/UML>
- Object Constraint Language (OCL), 2.4, February 2014, <https://www.omg.org/spec/OCL>
- System Modeling Language (SysML), 1.6, December 2019, <https://www.omg.org/spec/SysML>
- XMI Metadata Interchange (XMI), 2.5.1, June 2015, <https://www.omg.org/spec/XMI>

3.3 Other Normative References

- IEC 60812 for FMEA, <https://webstore.iec.ch/publication/26359> [accessed on October 28, 2020]
- IEC 61025 for FTA, <https://webstore.iec.ch/publication/4311> [accessed on October 28, 2020]
- IEC 61508:2010 for Functional safety of electrical/electronic/programmable electronic safety-related systems, <https://webstore.iec.ch/publication/22273> [accessed on October 28, 2020]
- International Standardization Organization. ISO PAS 21448:2019(en) Road vehicles – Safety of the intended functionality, <https://www.iso.org/standard/70939.html> [accessed on October 28, 2020]
- ~~International Standardization Organization. ISO 26262-1:2018 Road vehicles Functional safety - Part 1, Part 3. <https://www.iso.org/standard/68383.html> [accessed on June 19, 2023]~~
- N. Leveson and J. Thomas, STPA Handbook, Boston, MA: MIT, March 2018, https://psas.scripts.mit.edu/home/get_file.php?name=STPA_handbook.pdf [accessed on October 28, 2020]
- GSN specification 2, document number SCSC-141B <https://scsc.uk/gsn?page=gsn%202standard> [accessed on September 29, 2021]
- GSN metamodel mapping to SACM, https://scsc.uk/file/gc/GSN_metamodelV2-2-1210.pdf [accessed on October 7, 2021]
- ~~IEC 61078:2016, Reliability Block Diagrams, <https://webstore.iec.ch/publication/25647> [accessed on October 21, 2023]~~

Commented [AA4]: RAAML11-8

Deleted: International Standardization Organization. ISO 26262-1:2011(en) Road vehicles Functional safety - Part 1, Part 3. <https://www.iso.org/obp/ui/#iso:std:iso:26262:-1:ed-1:v1:en> [accessed on October 28, 2020]

Formatted: Font color: Text 1

Commented [AA5]: RAAML11-17

3.4 Informative References

- ISO/IEC 15288:2015, Systems Engineering - Systems Life Cycle Processes, https://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=63711 [accessed on October 28, 2020]
- International Council On Systems Engineering (INCOSE), Systems Engineering Handbook V4, 2015, <https://www.incose.org/products-and-publications/se-handbook> [accessed on October 28, 2020]
- National Institute of Standards and Technology, "NIST/Sematech Engineering Statistics Handbook", <https://www.itl.nist.gov/div898/handbook/> [accessed on October 21, 2023]

Formatted: Font color: Text 1

Commented [AA6]: RAAML11-17

4. Acknowledgements

The following companies and organizations submitted or supported parts of the original version of this standard:

Industry

- Dassault Systemes (submitter)
- Ford Motor Company (submitter)
- The Aerospace Corporation

Government

- NASA/Jet Propulsion Laboratory
- Commissariat à l'énergie atomique
- German Aerospace Center
- National Institute of Advanced Industrial Science and Technology (AIST)

Vendors

- No Magic owned by Dassault Systemes

Academia

- Massachusetts Institute of Technology

Liaisons

- Gesellschaft für Systems Engineering (submitter)
- MACE
- Assystem

The following persons were members of the team that designed and wrote this International Standard: Achim Weiss, Andreas Knapp, Andrius Armonas, Annelisa Sturgeon, Axel Berres, Christian Lalitsch-Schneider, Christoph Barchanski, Christopher Davey, Damun Mollahassani, Dave Banham, Edith Holland, Geoffrey Biggs, George Walley, Ilse Adamek, Jean-Francois Castet, Jianlin Shi, John Thomas, Kyle Post, Laura Hart, Manfred Koethe, Mark Sampson, Matthias Nagorni, Myron Hecht, Nataliya Yakymets, Rajiv Murali, Regis Casteran, Sarra Yako, Stephan Boutenko, Thomas Krynicki, Tim Weilkiens, Tomas Juknevičius, Vanessa Sehon, Victor Arcos Barraquero, Yan Liu.

For the final edition of the standard, the following people contributed: Andrius Armonas, Axel Berres, Dave Banham, Kyle Post, George Walley, Tomas Juknevičius.

5. Terms and Definitions

New terms and definitions have been required to create this specification. They are listed in the table below.

Table 5.1 – Description of terms and definitions used in this specification

Situation	A situation describes a set of situation occurrences of some type. The system, place, time, and state parameters are described by classifiers rather than individual descriptions. A situation occurrence is a system being in a given place at given time and in a given state. For example, “Boeing 747 with S/N 12305 is being refueled at Gate 7 of Amsterdam Schiphol at 11:45 on Monday, 30th of July 2018.”
Causality	Identifies cause-effect relationship between two situations. Causality could be direct (non-conditional), conditional, probabilistic or any other inter-situation relationship, defined by the user. Multiple situations can cause one situation and vice versa - one situation can cause multiple other situations. For example, a car in frequent contact with salt, causing safety-critical parts to corrode, which causes leaks in the brake line, causing the brakes to fail, causing a car accident, causing a passenger injury.
Relevant To	The Relevant To relationship is used to link situations to system model elements to provide context and relevance for the Situation. For example, in an insulin pump, a Situation where the insulin pump cannot be charged would be related to the main battery element in the system model.
Controlling Measure	A measure taken to address (mitigate severity, reduce probability of occurrence, increase probability of detection) a potential or real adverse situation.

6. Acronyms and Abbreviations

For the purposes of this specification, the following List of acronyms and abbreviations apply.

Table 6.1 – Description of acronyms used in this specification

ASIL	Automotive Safety Integrity Level
<u>CDF</u>	<u>Cumulative Distribution Function</u>
DET	Detectability
FMEA	Failure Mode and Effect Analysis
FTA	Fault Tree Analysis
GSN	Goal Structuring Notation
HARA	Hazard Analysis and Risk Assessment
HAZOP	A hazard and operability study
MBSE	Model-Based Systems Engineering
<u>MTBF</u>	<u>Mean Time Between Failures</u>
<u>MTTF</u>	<u>Mean Time to Failure</u>
<u>MTTR</u>	<u>Mean Time to Restore</u>
ISO	International Standardization Organization
OCC	Occurrence
OMG	Object Management Group
<u>PDF</u>	<u>Probability Density Function</u>
RAAML	Risk Analysis and Assessment Modeling Language
<u>RBD</u>	<u>Reliability Block Diagram</u>
RPN	Risk priority number
SEV	Severity
STPA	Systems Theoretic Process Analysis
SysML	Systems Modeling Language
UAF	Universal Architecture Framework
UML	Unified Modeling Language

Commented [AA7]: RAAML11-17

Commented [AA8]: RAAML11-17

Commented [AA9]: RAAML11-17

Commented [AA10]: RAAML11-17

7. Additional Information (non-normative)

7.1 Language Architecture

The RAAML specification reuses a subset of UML 2.5.1 and SysML 1.6 and provides additional extensions needed to address the Safety and Reliability for UML RFP (ad/2017-03-05) requirements. Those requirements form the basis for this specification. This document specifies the language architecture in terms of UML 2.5.1 and SysML 1.6. It explains the design principles and how they are applied to implement RAAML.

7.2 Philosophy

The RAAML working group uses a library approach heavily with a light UML profile support. Using model libraries has several significant benefits compared with implementing everything in a profile:

- It makes use of the full UML structural modeling capabilities instead of just using metamodeling, which are further limited by the UML prescriptions for stereotyping. The tools with good support for UML/SysML class and composite structure diagrams can make use of their existing generic functionality for modeling safety and reliability aspects of a system.
- It enables end users to extend the libraries and profiles provided by the specification because safety and reliability practices vary across domains (automotive, aerospace, nuclear, etc.) and organizations.
- Finally, it is typically easier to make modifications and extensions to model libraries than to profiles, as extensions occur at lower metalevels.

The RAAML development uses a model-driven approach. A simple description of the work process is:

- The specification is generated from the UML model used to describe RAAML. This approach allows the working group members to concentrate on architecture issues rather than documentation production. The UML tool automatically maintains consistency.

7.3 Principles of Creating, Editing, and Displaying of Composite Situations in Diagrammatic and Tabular Views

This standard uses UML/SysML structural modeling capabilities to capture safety and reliability data. The safety and reliability data are captured by a collection of scenarios and situations as shown in

Figure 7.1.




Figure 7.1 – Fundamental situation modeling principles

Complex scenarios can be built by inheriting from other scenarios and composing other situations as parts. Scenarios defined in libraries of this standard provide template scenarios from which to be inherited from. This way multilevel composite situations can be built.

- Situations are UML Classes, SysML Blocks.
- Scenario steps are captured using SysML parts - UML Properties with aggregation set to composite, and type set to sub-situation (which is UML Class, SysML Block); usually an association is also created for this property.
- Situation attribute values are captured using value properties - UML properties with type describing possible values (which is UML DataType, SysML ValueType) with the value specified in the defaultValue field.

When inheriting from library situations the properties of the user defined situations redefine or subset the properties of the library situation.

Note that user's model can have additional properties (including sub situations, and attributes and other kinds of properties), beyond those defined in the library. However, from the viewpoint of this standard, they carry user-specific extensions and are not relevant.

Situation in the user model can be inherited from the situation in the standard library indirectly through intermediate situations. This can be used to capture generality/specificity between the real-world situations being described and introduce user-specific library extensions.

Creation and Displaying of situation and scenario models can be done in diagrams, usual for UML/SysML tools, e.g., Class or Block Definition and Composite Structure or Internal Block diagrams. This suits rather well for the safety and reliability domains, which are used to graphical information input such as Fault Tree Analysis and Reliability Block Diagrams. However, users of many safety and reliability domains such as FMEA, STPA or ISO26262 are accustomed to tabular information input. Therefore, the principles of how these models can be described in a tabular format are explained in section §7.3.2.

Commented [AA11]: RAAML11-17

Deleted: This suits rather well for the safety and reliability domains, which are used to graphical information input such as Fault Tree Analysis.

7.3.1 Diagrammatic Situation Specification

Taking the operational situation TypicalAutomotiveSituation from ISO26262 library as an example, here is how the situation "Highway Driving Straight as Speed" would be defined in a diagram.

The ISO26262 library shown in (Figure 7.2) stipulates, that TypicalAutomotiveSituation is described by specifying trafficAndPeople, vehicleUsage, roadCondition, location, and environmentalCondition sub-situations and an Exposure attribute.




Figure 7.3 – User Model Defining Operational Situation “Highway Driving Straight at Speed”

7.3.2 Tabular Situation Specification

The same TypicalAutomotiveSituation, defined by the ISO26262 library and again shown in Figure 7.2, can also define a table format for entering automotive situation user model data in a tabular format.

The table for specifying typical automotive situations comprises the main Name column for defining the situation itself, plus one column per each attribute. A table for typical automotive situations, as defined by TypicalAutomotiveSituation library situation class would then have columns for Exposure, vehicleUsage, trafficAndPeople, location, roadCondition, and environmentalCondition. The column’s name does not need to follow library attributes strictly. They can be beautified, for the sake of user-friendliness. It is important that when the user adds or edits rows in this table, the underlying model data must be created in accordance with the chapters above.

The table below (Table 7.1) shows the same “Highway Driving Straight as Speed” situation defined in tabular format as in the previous chapter. Therefore, the underlying UML model structures must be the same as those shown in diagrammatic format (Figure 7.1).

Table 7.1 – Table for Specifying Operational Situations with Situation “Highway Driving Straight at Speed” Defined

#	Name	Exposure	Vehicle Usage	Traffic and People	Location	Road Condition	Environmental Condition
1	Highway Driving Straight at Speed	E4	Driving at Speed	Traffic Free Flow	Highway, City Roads		
1.1	Highway Driving Straight at Speed, Dangerous Conditions	E3	Driving at Speed	Traffic Free Flow	Highway, City Roads	Wet, Ice	Reduced Visibility

A typical safety and reliability domain such as ISO26262 will then use multiple tables, one for each of the structures defined in the library for that domain.

The tables can have additional columns, at the vendor's discretion, for specifying additional data about the situation, being described in a row. An example of such data could be a description (realized by e.g., UML Comment) of the situation.

Sub-classing by using a generalization relationship between situations can be expressed in tabular format, using hierarchical indented text in table row. In the above table, the "Highway Driving Straight at Speed, Dangerous Conditions" situation is a subclass of the "Highway Driving Straight at Speed" situation. Therefore, a generalization relationship is created between the two in the model. Note that the more specific situation can narrow down the field types of the parent. In this example, the sub-classing situation provides additional data for road and environmental conditions by using attributes and redefining attributes from the library. Using UML redefinition overrides the parent exposure to E3. The vehicle use, traffic and people, and location settings are inherited from the parent and do not require additional model elements.

In case of multiple composition levels between the situations defined in the library, it is possible to show multi-level composite situation data in a single table instead of the multiple interrelated tables by using hierarchical grouped column approach.

An example of using this hierarchical approach is shown for the main situation - HazardousEvent - in the library for ISO26262 standard (Figure 7.4):




Figure 7.4 – HazardousEvent Definition in the ISO26262 Library

The HazardousEvent comprises sub-situations hazard, systemLevelEffect, vehicleLevelEffect which are elementary and an accidentScenario which is a composite sub-situation. AccidentScenario is composed of the elementary malfunctioningBehavior and operationalSituation. OperationalSituation is composed of a multitude of operational condition sub-situations vehicleUsage, trafficAndPeople, location, roadCondition, and environmentalCondition.

If tabular format is used for entering this information, there could be 3 simple tables:

1. Table for operational situations, having columns for vehicleUsage, trafficAndPeople, location, roadCondition, and environmentalCondition.
2. Table for accident scenarios, having columns for malfunctioningBehavior and operationalSituation.

3. Table for hazardous events, having columns for hazard, systemLevelEffect, vehicleLevelEffect, and accidentScenario.

Alternatively, all this data can be entered in a single table, as shown in Table 7.2:

1. Table for hazardous events, having columns for **hazard**, **systemLevelEffect**, **vehicleLevelEffect**, and an **accidentScenario**.
 - 1.1. Accident scenario is a column group, comprising of columns **malfunctioningBehavior** and **operationalSituation**.
 - 1.1.1. Operational situation is a column group comprising of columns **vehicleUsage**, **trafficAndPeople**, **location**, **roadCondition**, and **environmentalCondition**.

Table 7.2 – Hazardous Event Table with Grouped Columns

Table 7-12: Hazardous Event Matrix with Grouped Columns											
Name	Hazard	Accident Scenario								System Level Effect	Vehicle Level Effect
		Malfunctioning Behavior	Operational Situation						Controllability		
			Vehicle Usage	Traffic and People	Location	Road Condition	Environmental Condition	Exposure			

Note – some columns (like ASIL level, or names of accident scenario, operational situation) have been skipped in the table for compactness reasons; in the actual tool that is not limited by page width they would be present.

8. Diagram Legend (non-normative)

The section 9 is comprised of diagrams that represent elements from the RAAML 1.0 specification. The diagrams are color-coded to help the reader to understand the model easier. Please refer to the legend in Figure 8.1 to understand the diagrams.



Diagram shapes color-coded using gray color represent elements belonging to other packages than the one being specified in the current diagram.



Diagram shapes color-coded using white color represent elements belonging to packages that are being specified in the current diagram.

Figure 8.1 – Legend of color codes

An example in Figure 8.2 demonstrates how legends are used. Elements that belong to FTA (Fault Tree Analysis) library will be represented in white color in diagrams which belong to FTA method specification. Other elements like DysfunctionalEvent will be represented in gray since they belong to the General part of the specification.




Figure 8.2 – An example of using a legend

This page intentionally left blank.

9. Risk Analysis and Assessment Modeling Language (RAAML) Library and Profile

The RAAML library and profile imports the entire SysML profile. The use of this import is intended to provide more seamless integration with system modeling using SysML and to be able to fully leverage the capabilities of SysML.

9.1 Core

The core concepts domain model is depicted in Figure 9.1. The submission team uses this domain model to derive the CoreLibrary and CoreProfile packages (specified in sections 9.1.1 and 9.1.2 respectively). The other libraries and profiles of the specification are based on the CoreLibrary and CoreProfile packages and contain elements and relationships representing concepts common across safety and reliability analysis methods.




Figure 9.1 – Core concepts domain model

The central element in the core concepts domain model is the “Situation” concept. A situation occurrence is defined as a system being in a given place at given time and in a given state. For example, “Boeing 747 with S/N 12305 is being refueled at Gate 7 of Amsterdam Schiphol at 11:45 on Monday, 30th of July 2018.” An elementary situation is a classifier. It describes a set of situation occurrences of some type. The system, place, time, and state parameters are described by classifiers rather than individual descriptions.

When describing a situation, some of its parameters may be omitted if the situation does not need to be specific with respect to that parameter. For example:

- Fire in the engine compartment of the ship.
- Finger injury of the circular saw operator.

Different Situations can have generalization/specialization relationships between them. Generalization between two situations expresses the subset/superset relationship between the sets of occurrences that these situations represent. For example, “bone fracture” may be defined as a subtype of “Injury”.


Situations can have quantitative attributes, such as probability of occurrence. These are defined using the DependabilityAttribute class. Quantitative attributes can be related to each other and to attributes of the system by formulae using the AttributeRelation class. Formulae can be expressed in any language that the modeling tool can compute, including OCL and other executable languages. For example:

$$\text{FMEAItem.RiskPriorityNumber} = \text{Cause.Occurrence} \times \text{FailureMode.Detectability} \times$$

Effect.Severity

Different Situations can be associated with each other using the Causality class, expressing semantic relationships between situations such as simple causality, conditional causality, and probabilistic connections. These relations may also have quantitative attributes, such as the probability of occurrence of the “to” situation if the “from” situation occurs.

Commented [AA12]: RAAML11-11



Deleted:

For example, a car in frequent contact with salt, causing safety-critical parts to corrode, which causes leaks in the brake line, causing the brakes to fail, causing a car accident, causing a passenger injury.

A non-elementary situation (the “Composition” relationship in Figure 9.1) is a concept encompassing multiple elementary situations: a single system or combination of several systems in a mutable layout, flowing in time through a sequence of states. The choice of whether to use a composite situation with parts described by subsituations, or to use a single situation, is at the discretion of the modeler. It depends on the modeler's needs, such as the depth of analysis required.

Situations can violate requirements, constraints defined/prescribed for the system, or other specifications describing how the system should operate. For example, a Situation where the system can-not detect glucose level violates the requirement that “the insulin pump must work for 1 week without the need to replace batteries”.

The RelevantTo relationship is used to link situations to system model elements to provide context and relevance for the Situation. For example, in the aforementioned insulin pump, a Situation where the insulin pump cannot be charged would be related to the main battery element in the system model.

Situations can be mitigated, detected, and prevented via the **ControllingMeasure**. The use of this relationship introduces new safety requirements.

Deleted: ControllingAction

Commented [AA13]: RAAML11-11

It was decided early on to reuse as many concepts from the SysML language as possible and only add concepts that are missing in SysML to address safety and reliability aspects of systems. This avoids duplication between two languages that will typically be used together. It also enables tool vendors to implement the new profile and library without requiring new tool capabilities, assuming SysML is supported. This leads to a very small library and profile on top of SysML/UML being sufficient to cover all core concepts. The core domain model is covered by SysML/UML concepts as shown in Table 1. The CoreLibrary package is specified in section 9.1.1. The CoreProfile package is shown in 9.1.2. The Core profile and library are used by all domain-specific methods in the specification.

Table 9.1 – Mapping of core concepts to the SysML/UML language

Core concept	SysML/UML concept
Situation	A specialization of a Block in SysML and a new stereotype «Situation»
DependabilityAttribute	SysML Value Property
AttributeRelation	SysML Constraint Block
Generalization	UML Generalization relationship
Composition	UML Composition relationship
Violates	A stereotyped UML dependency
RelevantTo	A stereotyped UML dependency
Causality	An association/connector combination
ControllingMeasure	A stereotyped UML dependency

Commented [AA14]: RAAML11-11

Deleted: ControllingAction

9.1.1 Core::Core Library

AnySituation

Package: Core Library

isAbstract: Yes

Applied Stereotype: «Situation»

Description

AnySituation is the universal root of all situations. All situations inherit from AnySituation. A situation describes a set of situation occurrences of some type. The system, place, time, and state parameters are described by classifiers rather than individual descriptions. A situation occurrence is a system being in a given place at given time and in a given state.

For example, “Boeing 747 with S/N 12305 is being refueled at Gate 7 of Amsterdam Schiphol at 11:45 on Monday, 30th of July 2018.”




Figure 9.2 – AnySituation

Attributes

from : AnySituation[0..*] (member end of Causality association)	A situation which precedes the one at the other end of the Causality relationship.
to : AnySituation[0..*] (member end of Causality association)	A situation which follows the one at the other end of the Causality relationship.

Causality

Package: Core Library

Description

Universal root relationship between situations. All situation relationships inherit from this relationship. Identifies cause and effect relationship between two situations. Causality could be direct (non-conditional), conditional or probabilistic or any other inter-situation relationship, defined by the user. Multiple situations can cause one situation and vice versa - one situation can cause multiple other situations.

For example, a car in frequent contact with salt, causing safety-critical parts to corrode, which causes leaks in the brake line, causing the brakes to fail, causing a car accident, causing a passenger injury.




Figure 9.3 – Causality

Association ends

to : AnySituation[0..*] (member end of Causality association)	A situation which follows the one at the other end of the Causality relationship.
from : AnySituation[0..*] (member end of Causality association)	A situation which precedes the one at the other end of the Causality relationship.

9.1.2 Core::Core Profile

Situation

Package: Core Profile
isAbstract: No
Generalization: Block
Extension: Class

Description

A situation is a SysML v1.6 Block. The situation reuses the following functionality from the Block concept: generalizations, parts, value properties, and Parametrics. The situation stereotype is only needed to distinguish situations from other types of blocks. See [AnySituation](#) for the definition of a situation concept.




Figure 9.4 – Situation

RelevantTo

Package: Core Profile
isAbstract: No
Generalization: DirectedRelationshipPropertyPath
Extension: Dependency

Description

The RelevantTo relationship is used to link situations to system model elements to provide context and relevance for the Situation. For example, in an insulin pump, a Situation where the insulin pump cannot be charged would be related to the main battery element in the system model. The RelevantTo relationship reuses the following functionality from the DirectedRelationshipPropertyPath concept: targetContext and targetPropertyPath.




Figure 9.5 – RelevantTo

Constraints

[1] ClientIsSituation -- client of the RelevantTo must be a Situation
 Situation.allInstances().base_Class->includesAll(self.base_Dependency.client)

ControllingMeasure

Package: Core Profile
isAbstract: Yes
Generalization: DirectedRelationshipPropertyPath
Extension: Dependency

Description

A measure taken to address (mitigate severity, reduce probability of occurrence, increase probability of detection) a potential or real adverse situation.




Figure 9.6 – ControllingMeasure

Attributes

affects : Property[0..*] Indicates that this controlling measure influences (typically improves) a particular quantitative attribute of the situation.

Constraints

[1] SupplierIsSituation -- supplier of the ControllingMeasure must be a Situation
 Situation.allInstances().base_Class->includesAll(self.base_Dependency.supplier)

Violates

Package: Core Profile
isAbstract: No
Extension: Dependency

Description

The violates relationship indicates a situation where a system is violating a prescription (requirement, constraint, etc.). It is used to connect situations to requirements, design constraints and any other elements of system models which prescribe a characteristic of the system.

For example, a Situation where the insulin pump drains the battery in 3 days violates the requirement that “The system must work for 1 week without the need to replace batteries”.




Figure 9.7 – Violates

Constraints

```
[1] ClientIsSituation      -- client of the Violates must be a Situation
                          Situation.allInstances().base_Class->includesAll(self.base_Dependency.client)
```

IDCarrier

Package: ISO 26262 Profile

isAbstract: No

Extension: Element

Description

Additional stereotype for carrying human-readable identification data.




Figure 9.8 – IDCarrier

Attributes

Id : String[1] Human readable identifier.

9.2 General

The specification includes a general safety and reliability package that extends the core package. It defines common concepts that are used or extended in the method- and domain-specific reliability and safety packages. The package provides a model library, specified in section 9.2.1, and a profile, specified in section 9.2.2.

The general concepts contained in this package can be used as-is to model the safety and reliability related aspects of a system. However, the intended purposes of the package are as follows:

1. Provide a common base for the method- and domain-specific reliability and safety modeling packages. The same concepts are used in a number of safety and reliability techniques (such as FMEA and FTA), so the role of this package is to prevent duplication of common concepts in other packages. This also enables movement of information between domains for cross-domain issues. This is particularly important as different domains may use the same concepts with different vocabulary. A common foundation provides a way to translate between these.

2. Provide traceability links between safety and reliability artefacts across the system life cycle. For example, the failure modes defined during Hazard Analysis and Risk Assessment (HARA, defined in the ISO 26262 package) and in an FMEA could be traced and considered during an FTA.
3. Provide a foundation on which additional methods, techniques and domains with safety and reliability concerns not currently included in the profile can be built by users. For example, a tool vendor could build an additional package for the railway domain by building on the general safety and reliability foundation. This both reduces effort to introduce an additional domain and allows additional domain packages to be compatible with the existing specification content.

9.2.1 General::General Concepts Library

AbstractEvent

Package: General Concepts Library

isAbstract: Yes

Generalization: [AnySituation](#)

Applied Stereotype: «[Situation](#)»

Description

Anything that causes a change in a system under analysis or environment. Event has an identifiable starting point in time.




Figure 9.9 – AbstractEvent

Attributes

likelihood : [1]

A placeholder attribute for indicating likelihood of occurrence of an event. It is intentionally left without a type. Method developers can derive more specialized ways to characterize likelihood.

AbstractCause

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractEvent](#), [Factor](#)

Applied Stereotype: «[Situation](#)»

Description

An AbstractCause is a precursor [event](#) that activates other [events](#). The AbstractCause is a root class for all kinds of causes; method developers should derive from it more specific kinds of causes with specific types for [occurrence](#) property. One case is demonstrated in the [Cause](#) element that redefines the occurrence property of the AbstractCause with the type Real.

See the diagram [GeneralConceptsLibrary](#).

Commented [AA15]: RAAML11-28

See also: [fault](#) association end of the [Activation](#) association.




Figure 9.10 – AbstractCause

Attributes

occurrence : [1], redefines [likelihood](#)

A placeholder attribute without a type declared, for indicating how often this situation occurs. It is a redefinition of [likelihood](#).

premitigationOccurrences : [0..*]

A placeholder attribute for indicating how often this situation occurred prior to mitigation. This property can have more than one value.

Cause

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractCause](#)

Applied Stereotype: [«Situation»](#)

Description

A Cause is a specific implementation of [AbstractCause](#) that defines [occurrence](#) property with the type Real.




Figure 9.11 – Cause

Attributes

occurrence : Real[1], redefines [occurrence](#)

An attribute with the type Real, for indicating how often this situation occurs.

premitigationOccurrences : Real[0..*],
redefines [premitigationOccurrences](#)

An attribute for indicating how often this situation occurred prior to mitigation. This property can have more than one value.

DysfunctionalEvent

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractEvent](#)

Applied Stereotype: «Situation»

Description

An event whose occurrence can cause a dysfunctional behavior of a system or a part of the system.

The DysfunctionalEvent concept is a generalization of such concepts as failure, feared event, etc. that are considered in the domain-specific safety standards. It might be extended for introducing new safety and reliability methods and techniques.




Figure 9.12 – DysfunctionalEvent

AbstractFailureMode

Package: General Concepts Library

isAbstract: Yes

Generalization: [UndesiredState](#)

Applied Stereotype: «FailureMode»

Description

The manner in which a system or part of a system (e.g., functions, components, hardware, software, hardware parts, software units), can fail (ISO 26262-1:2018, definition 3.51, modified).

The AbstractFailureMode is a root class for all failure modes; method developers should derive more specific kinds of failure modes with specific types for the [detectability](#) property. One case is demonstrated in the [FailureMode](#) element that redefines the detectability property of the AbstractFailureMode with the type Real.




Figure 9.13 – AbstractFailureMode

Attributes

detectability : [1]

A placeholder attribute without a type declared, for indicating how easy it is to detect this failure mode.

premitigationDetectabilities : [0..*]

A placeholder attribute for indicating how easy it would have been to detect the situation with the previous design iteration. This property can have more than one value.

FailureMode

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractFailureMode](#)

Applied Stereotype: [«FailureMode»](#)

Description

FailureMode is a specific implementation of [AbstractFailureMode](#) that defines the [detectability](#) property with the type Real.

A failure is an instance of a FailureMode.




Figure 9.14 – FailureMode

Attributes

detectability : Real[1], redefines

[detectability](#)

An attribute with the type Real, for indicating how easy it is to detect the situation.

premitigationDetectabilities : Real[0..*],

redefines [premitigationDetectabilities](#)

An attribute for indicating how easy it would have been to detect the situation with the previous design iteration. This property can have more than one value.

AbstractEffect

Package: General Concepts Library

isAbstract: Yes

Generalization: [DysfunctionalEvent](#)

Applied Stereotype: [«Situation»](#)

Description

An AbstractEffect is a [DysfunctionalEvent](#) that is a result or a consequence of another [Situation](#). The AbstractEffect is a root class for all effects; method developers should derive more specific kinds of effects with specific types for the [severity](#) property.

One case is demonstrated in the [Effect](#) element that redefines the severity property of the AbstractEffect with the type Real.

See the diagram [GeneralConceptsLibrary](#).

See also: [ErrorPropagation](#), [ErrorRealization](#) associations.




Figure 9.15 – AbstractEffect

Attributes

severity : [1]

A placeholder attribute without a type declared, for indicating the estimate of the extent of harm.

premitigationSeverities : [0..*]

A placeholder attribute for indicating the estimate of the extent of harm that would have resulted from the previous design iterations. This property can have more than one value.

Effect

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractEffect](#)

Applied Stereotype: «Situation»

Description

An Effect is a specific implementation of [AbstractEffect](#) that defines the [severity](#) property with the type Real.




Figure 9.16 – Effect

Attributes

severity : Real[1], redefines [severity](#)

An attribute with the type Real, for indicating the estimate of the extent of harm.

premitigationSeverities : Real[0..*], redefines [premitigationSeverities](#)

An attribute for indicating the estimate of the extent of harm that would have resulted from the previous design iterations. This property stores more than one value.

Activation

Package: General Concepts Library

Generalization: [Causality](#)

Description

A [causal](#) relationship describing the propagation of the initial [AbstractCause](#) situation to the [DysfunctionalEvent](#) situation in the system.




Figure 9.17 – Activation

Association ends

error : DysfunctionalEvent[0..*] The dysfunctional situation (error) of the system.
(member end of [Activation](#) association, redefines [to](#))

fault : AbstractCause[0..*] (member end of [Activation](#) association, redefines [from](#)) The causal fault.

ErrorPropagation

Package: General Concepts Library

Generalization: [Causality](#)

Description

A [causal](#) relationship describing the propagation of [errors](#) (one error leading to another) throughout the system.




Figure 9.18 – ErrorPropagation

Association ends

toError : DysfunctionalEvent[0..*] The successor error.
 (member end of [ErrorPropagation](#)
 association, redefines [to](#))

fromError : DysfunctionalEvent[0..*] The predecessor error.
 (member end of [ErrorPropagation](#)
 association, redefines [from](#))

ErrorRealization

Package: General Concepts Library

Generalization: [Causality](#)

Description

A [causal](#) relationship describing the propagation of an [error](#) to a [failure](#).




Figure 9.19 – ErrorRealization

Association ends

failure : DysfunctionalEvent[0..*] The resulting failure.
 (member end of [ErrorRealization](#)
 association, redefines [to](#))

error : DysfunctionalEvent[0..*] The predecessor error.
 (member end of [ErrorRealization](#)
 association, redefines [from](#))

HarmPotential

Package: General Concepts Library

isAbstract: Yes

Generalization: [AnySituation](#)

Applied Stereotype: «Situation»

Description

A state where there is the potential of [harm](#). This includes all types of harm arising from malicious or non-malicious causes.




Figure 9.20 – HarmPotential

Hazard

Package: General Concepts Library

isAbstract: Yes

Generalization: [HarmPotential](#)

Applied Stereotype: «Situation»

Description

A potential source of [harm](#) (IEC 61508-4, 3.1.2). Source of harm is non-malicious.

The term includes danger to persons arising within a short time scale (for example, fire and explosion) and also those that have a long-term effect on a person's health (for example, release of a toxic substance).




Figure 9.21 – Hazard

Scenario

Package: General Concepts Library

isAbstract: Yes

Generalization: [AnySituation](#)

Applied Stereotype: «Situation»

Description

A composite [situation](#), consisting of multiple steps (that are themselves [situations](#)). Steps should have causal ordering, indicated by [Causality](#) relationships or sub-types thereof.




Figure 9.22 – Scenario

Attributes

scenarioStep : AnySituation[0..*] (member end of association)

AbstractRisk

Package: General Concepts Library

isAbstract: Yes

Generalization: [Scenario](#)

Applied Stereotype: «Situation»

Description

An [AbstractRisk](#) is a [Scenario](#) - combination of harm potential ([Hazard](#) or Vulnerability), triggering event ([AbstractEvent](#)), and resulting harm ([AbstractEffect](#)).

The [AbstractRisk](#) is a placeholder to enable modelers to specify methodology-specific kinds of risks.




Figure 9.23 – AbstractRisk

Attributes

score :

Combination of the probability of occurrence of abstract event resulting from abstract harm and the severity of that harm (IEC 61508-4, 3.1.5, modified).

An example could be risk priority number ([RPN](#)) in FMEA analysis.

trigger : AbstractEvent[0..*] (member end of association, subsets [scenarioStep](#))

Triggering event ([AbstractEvent](#)) which causes harm to materialize.

harm : AbstractEffect[0..*] (member end of association, subsets [scenarioStep](#))

Resulting harm ([AbstractEffect](#)).

harmPotential : HarmPotential[0..*]
(member end of association, subsets
[scenarioStep](#))

Pre-existing risk ([HarmPotential](#)).

UndesiredState

Package: General Concepts Library

isAbstract: Yes

Generalization: [DysfunctionalEvent](#)

Applied Stereotype: «Situation»

Description

An element's condition as a specific time which represents an unintended situation.




Figure 9.24 – UndesiredState

Limitation

Package: General Concepts Library

isAbstract: Yes

Generalization: [Factor](#)

Applied Stereotype: «Situation»

Description

A limiting condition; restrictive weakness; lack of capacity; inability or handicap.
Limitation is a restriction of Capability.




Figure 9.25 – Limitation

Loss

Package: General Concepts Library

isAbstract: Yes

Generalization: [AbstractEffect](#)

Applied Stereotype: «Situation»

- Formatted: Font: 10 pt, Not Bold
- Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt
- Formatted: Font: Not Bold
- Formatted: Font: 10 pt, English (United Kingdom)
- Formatted: Default Paragraph Font
- Formatted: OMG Normal Paragraph, Space After: 0 pt

- Formatted: Font: 9 pt
- Formatted: Font: 10 pt, Not Bold
- Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Description

In STPA, is any effect that is unacceptable and should be prevented. Some factors such as environmental conditions may contribute to a loss but are outside our control. Examples for losses are:

- Loss of human life or injury
- Vehicle/property damage
- Mission loss (inadequate transportation)
- Loss of customer satisfaction
- Financial loss
- Loss of public image
- Environmental pollution

Formatted: English (United Kingdom)

Formatted: OMG Normal Paragraph

Formatted: OMG Normal Paragraph, Space After: 0 pt, Add space between paragraphs of the same style, Line spacing: single, Bulleted + Level: 1 + Aligned at: 0.25" + Indent at: 0.5"




Figure 9.26 – Loss

Formatted: Font: 9 pt

Factor

Package: General Concepts Library
isAbstract: Yes

Generalization: AnySituation

Applied Stereotype: «Situation»

Description

A situation that contributes to a result or outcome

Formatted: Font: 10 pt

Formatted: Default Paragraph Font, Font: (Default) Courier New




Figure 9.27 – Factor

Commented [AA16]: RAAML11-28

Formatted: Font: 9 pt

Formatted: Body Text

9.2.2 General::General Concepts Profile

FailureMode

Package: General Concepts Profile

isAbstract: No

Generalization: [Situation](#)

Extension: Class

Description

See [FailureMode](#) library class for the definition of a situation concept.

The [FailureMode](#) stereotype is only needed to distinguish FailureModes from other types of situations.




Figure 9.28 – FailureMode

Error

Package: General Concepts Profile

isAbstract: No

Generalization: [Situation](#)

Extension: Class

Description

The discrepancy between a computed, observed, or measured value or condition and the true, specified or theoretically correct value or condition. [IEC 61508-4, 3.6.11].

The [Error](#) stereotype is needed to distinguish this type of situations.




Figure 9.29 – Error

Fault

Package: General Concepts Profile

isAbstract: No

Generalization: [Situation](#)

Extension: Class

Description

Abnormal condition that may cause a reduction in, or loss of, the capability of a functional unit to perform a required function. [IEC 61508-4, 3.6.1].

Abnormal or undesired condition that can cause an element or a system to fail. [ISO 26262-1:2018, 3.54, modified]

The [Fault](#) stereotype is needed to distinguish this type of situations.




Figure 9.30 – Fault

Detection

Package: General Concepts Profile

isAbstract: No

Generalization: [ControllingMeasure](#)

Extension: Dependency

Description

A kind of [ControllingMeasure](#) taken to increase probability of detecting the situation under analysis. In hardware these measures may include built-in diagnostic tests, or physical inspection and manual tests.




Figure 9.31 – Detection

Prevention

Package: General Concepts Profile

isAbstract: No

Generalization: [ControllingMeasure](#)

Extension: Dependency

Description

A kind of [ControllingMeasure](#) taken to reduce probability of occurrence of the situation under analysis.




Figure 9.32 – Prevention

Mitigation

Package: General Concepts Profile

isAbstract: No

Generalization: [ControllingMeasure](#)

Extension: Dependency

Description

A kind of [ControllingMeasure](#) taken to reduce severity of the situation under analysis.




Figure 9.33 – Mitigation

Recommendation

Package: General Concepts Profile

isAbstract: No

Generalization: [ControllingMeasure](#)

Extension: Dependency

Description

Recommendation is used to connect the situation to an action item.

An action item is normally a Requirement, but it can be a less "strong" type of advice - comment, rationale, etc.

The requirement is further managed by the requirements management system - it can have responsible persons, due date, verification properties etc.




Figure 9.34 – Recommendation

FailureState

Package: General Concepts Profile

isAbstract: No

Extension: State

Description

State, which the system or a part of the system enters after occurrence of [FailureMode](#) (failure).

The Failure state concept might be used in various formal safety and reliability analysis methods based on the state machine notation. Failure states could be tied to [FailureModes](#) via the [RelevantTo](#) dependency.




Figure 9.35 – FailureState

Undeveloped

Package: General Concepts Profile

isAbstract: No

Extension: Element

Description

Undeveloped stereotype is meant to identify incomplete concepts.

This stereotype can be applied in combination with Goal or Strategy stereotype to express the fact that the goal or strategy is not fully developed, and therefore may lack crucial details.

This stereotype can also be applied to basic event in fault trees to express the fact that it is not fully developed.

Hazard

Package: General Concepts Profile

isAbstract: No

Generalization: Situation

Extension: Class

Commented [AA17]: RAAML11-28

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Description

A marker stereotype for hazards (see the [Hazard](#) library element for definition).




Figure 9.36 – Hazard

Item

Package: General Concepts Profile

isAbstract: Yes

Extension: Element

Description

An item defines a notional boundary for a risk analysis.




Figure 9.37 – Item

Attributes

member : Element[0..*]

boundaryMember : Element[0..*], subsets member

Elements that are inside the boundary of an item.

Elements that are on the boundary of an item. They act as interaction points between inside and outside of the item.

PresentIn

Package: General Concepts Profile

isAbstract: No

Generalization: RelevantTo

Extension: Dependency

Description

Formatted: English (United Kingdom)

Formatted: English (United Kingdom)

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font, Font: Not Bold, English (United Kingdom)

Formatted: OMG Normal Paragraph, Space After: 0 pt

Formatted: Font: (Default) Arial, 10 pt, Not Bold

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font, Font: Not Bold, English (United Kingdom)

Formatted: OMG Normal Paragraph, Space After: 0 pt

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Declares that a specific situation (e.g. weakness, vulnerability) is persistent when the part/block is included in the system.




Figure 9.38 – PresentIn

SingleElementItem

Package: General Concepts Profile
isAbstract: No

Generalization: Item

Extension: Class

Description

An item that is defined by an individual block.




Figure 9.39 – SingleElementItem

Attributes

member : Element[0..*], redefines member

This is a redefinition of Item::member. When the item is defined by an individual block, this property collects features of this block.

referencedElement : Element[1]

A reference to a block defining the item.

ElementGroupBasedItem

Package: General Concepts Profile
isAbstract: No

Generalization: ElementGroup, Item

Formatted: Default Paragraph Font, Font: Not Bold, English (United Kingdom)

Formatted: OMG Normal Paragraph, Space After: 0 pt

Formatted: Font: (Default) Arial, 10 pt, Not Bold

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Default Paragraph Font, Font: Not Bold, English (United Kingdom)

Formatted: OMG Normal Paragraph, Space After: 0 pt

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Extension: Comment

Description

An item that is defined by a set of elements using the SysML element group mechanism.




Figure 9.40 – ElementGroupBasedItem

Attributes

member : Element[0..*], redefines member, member The members of the group are specified by SysML ElementGroup::member.

9.3 General Security

9.3.1 General Security::General Security Concepts Library

Threat

Package: General Security Concepts Library isAbstract: Yes

Generalization: HarmPotential

Applied Stereotype: «Situation»

Description

A Threat is any circumstance or event (Situation in RAAML) with the potential to adversely impact Assets.

Formatted: Default Paragraph Font, Font: Not Bold, English (United Kingdom)

Formatted: OMG Normal Paragraph, Space After: 0 pt

Formatted: Outline numbered + Level: 2 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Outline numbered + Level: 3 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: (Default) Times New Roman, 10 pt

Formatted: Default Paragraph Font, Font: (Default) Courier New

A Threat is the potential cause of unacceptable asset loss and the undesirable consequences or impact of such a loss.

Formatted: Font: (Default) Times New Roman
Formatted: Font:
Formatted: HTML Preformatted, Space After: 10 pt




Figure 1.41 - Threat

Weakness

Package: General Security Concepts Library
isAbstract: No


Generalization: Limitation

Applied Stereotype: «Situation»

Description

A “weakness” is a condition under certain circumstances, could contribute to the introduction of Vulnerabilities.

Formatted: Font: 9 pt
Formatted: Font: 9 pt
Formatted: Font: 9 pt
Formatted: Font: 9 pt
Formatted: Font: 9 pt
Formatted: Font: 10 pt, Not Bold
Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt



Formatted: Font: (Default) Times New Roman, 10 pt
Formatted: Default Paragraph Font, Font: (Default) Courier New

Figure 1.42 - Weakness

Vulnerability

Package: General Security Concepts Library
isAbstract: No

Generalization: Limitation

Applied Stereotype: «Situation»

Description

A Weakness that can be exploited or triggered by a SecurityActor to produce an undesirable behavior (DysfunctionalEvent).

Vulnerability can then be used as a (exploit)scenario step.

Formatted: Font: 10 pt, Not Bold
Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font:
Formatted: Font: (Default) Times New Roman, 10 pt
Formatted: Font: (Default) Times New Roman
Formatted: Default Paragraph Font, Font: (Default) Courier New




Figure 1.43 - Vulnerability

9.3.2 General Security::General Security Concepts Profile

Threat

Package: General Security Concepts Profile
isAbstract: No

Generalization: Situation

Extension: Class

Description

A marker stereotype for Threat.




Figure 1.44 - Threat

Impacts

Package: General Security Concepts Profile
isAbstract: No

Generalization: RelevantTo

Extension: Dependency

Description

How a particular Situation affects the properties of an Asset




Figure 1.45 - Impacts

Attributes

Formatted: Outline numbered + Level: 3 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Default Paragraph Font

Formatted: Normal, Space After: 0 pt

affects : Property[0..1] Indicates which aspect of the asset (e.g. financial, or operational etc.) is being impacted.

rating : [0..1] Rating of the Impact on the Asset

Asset

Package: General Security Concepts Profile

isAbstract: No

Extension: Class

Description

An Asset represents anything that has value to a person or organization.

Asset can be contextualized by the Item.

For that, the recommended way is to create Asset-typed property in the appropriate Item.

Note: this only works for the Item flavors that are based on UML Class. If there are methodologies that have custom kinds of items, not based on UML Class, those methodologies need to specify their own mechanisms to contextualize the Asset




Figure 1.46 - Asset

Valuates

Package: General Security Concepts Profile

isAbstract: No

Generalization: DirectedRelationshipPropertyPath

Extension: Dependency

Description

Relationship connecting Asset description with the underlying system model element.




Figure 1.47 - Valuates

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: (Default) Times New Roman, 10 pt, English (United States)

Formatted: Default Paragraph Font, Font: (Default) Courier New, English (United States)

SecurityActor

Package: General Security Concepts Profile

isAbstract: No

Extension: Classifier

Description

A SecurityActor represents an entity that has the potential to affect a Risk - typically a threat actor.




Figure 1.48 - SecurityActor

PresentedBy

Package: General Security Concepts Profile

isAbstract: No

Generalization: RelevantTo

Extension: Dependency

Description

Presentation/Initiation of a Situation by a SecurityActor.




Figure 1.49 - PresentedBy

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: (Default) Times New Roman, 10 pt, English (United States)

Formatted: Font: (Default) Times New Roman, English (United States)

Formatted: Default Paragraph Font, Font: (Default) Courier New, English (United States)

Formatted: Font: 10 pt, Not Bold

Formatted: OMG Heading 5, None, Space Before: 0 pt, After: 0 pt

Formatted: Font: (Default) Times New Roman, 10 pt, English (United States)

Formatted: Font: (Default) Times New Roman, English (United States)

Formatted: Default Paragraph Font, Font: (Default) Courier New, English (United States)

Commented [AA18]: RAAML11-28

9.4 Methods::FMEA

The Failure Mode and Effects Analysis (FMEA) is a method of inspecting a system to analyze potential failures. Therefore, as many components, assemblies, and subsystems as possible are examined in order to identify these failure modes in a system and their causes and effects.

9.4.1 Methods::FMEA::FMEALibrary

AbstractFMEAItem

Package: FMEALibrary

isAbstract: Yes

Generalization: [AbstractRisk](#)

Applied Stereotype: «FMEAItem»

Description

An AbstractFMEAItem is a scenario (more specifically - [AbstractRisk](#) scenario) composed of a failure mode, (potentially multiple) cause(s) and effect(s). It stores assessed and mitigated risk priority numbers.




Figure 9.50 – AbstractFMEAItem

Attributes

RPN : [1], redefines [score](#)

The risk priority number ranks the risk of the FMEA item. It is a specialization of [AbstractRisk::score](#).

failureMode : AbstractFailureMode[1] (member end of association, subsets [scenarioStep](#))

Represents the failure mode which is reached if a system element fails.

cause : AbstractCause[1..*] (member end of association, subsets [scenarioStep](#))

Represents the cause of the failure of a system element.

finalEffect : AbstractEffect[1..*] (member end of association, redefines [harm](#))

Represents the effect which occurs on the system border.

previousRPNValues : [0..*]

Represents the assessed risk priority number before mitigating the risk of a failure.

harmPotential : HarmPotential[0] (member end of association, redefines [harmPotential](#), subsets [scenarioStep](#))

Pre-existing risk. Not used in FMEA method, therefore redefined in this library with multiplicity [0]

FMEItem

Package: FMEALibrary

isAbstract: Yes

Generalization: [AbstractFMEItem](#)

Applied Stereotype: «FMEItem»

Description

A FMEItem is a specialization of [AbstractFMEItem](#) with the Real implementation of quantitative attributes.




Figure 9.51 – FMEItem

Attributes

finalEffect : Effect[1..*] (member end of association, redefines [finalEffect](#))

cause : Cause[1..*] (member end of association, redefines [cause](#))

RPN : Real[1], redefines [RPN](#)

failureMode : FailureMode[1] (member end of association, redefines [failureMode](#))

calculation : RPNCalculation

previousRPNValues : Real[0..*], redefines [previousRPNValues](#)

The specialization of [AbstractFMEItem](#) :: [finalEffect](#) with the implementation of [Effect](#) with Real severity.

The specialization of [AbstractFMEItem](#) :: [cause](#) with the implementation of [Cause](#) with Real occurrence.

The specialization of [AbstractFMEItem](#) :: [RPN](#) with the type Real.

The specialization of [AbstractFMEItem](#) :: [failureMode](#) with the implementation of [FailureMode](#) with Real detectability.

Link to a formula for [RPN](#) calculation.

The specialization of [AbstractFMEItem](#) :: [previousRPNValues](#) with the type Real.

RPNCalculation

Package: FMEALibrary

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

A formula for [RPN](#) calculation. This implementation uses multiplication of Occurrence x Detectability x Severity to calculate RPN.

Attributes

RPN :	Risk priority number
SEV :	Severity
OCC : Real	Occurrence
DET :	Detectability

Constraints

[1]	Reduced priority number is calculated by simple multiplication of Severity, Detectability and Occurrence.
-----	---

LossOfFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: [«FailureMode»](#)

Description

A failure mode representing loss of function e.g., the function is inoperable, or suddenly fails.




Figure 9.52 – LossOfFunction

DegradationOfFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: [«FailureMode»](#)

Description

A failure mode representing a degradation of function or loss of function over time.




Figure 9.53 – DegradationOfFunction

IntermittentFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: «FailureMode»

Description

A failure mode representing an intermittent function or the random stops and starts of a function.




Figure 9.54 – IntermittentFunction

PartialFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: «FailureMode»

Description

A failure mode representing a partial function or loss of performance.




Figure 9.55 – PartialFunction

UnintendedFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: «FailureMode»

Description

A failure mode representing an unintended function, function operating at the wrong time, with unintended direction, or unequal performance.




Figure 9.56 – UnintendedFunction

ExceedingFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: [«FailureMode»](#)

Description

A failure mode representing a function exceeding the acceptable operational performance.




Figure 9.57 – ExceedingFunction

DelayedFunction

Package: FMEALibrary

isAbstract: Yes

Generalization: [FailureMode](#)

Applied Stereotype: [«FailureMode»](#)

Description

A failure mode representing a delayed function or function operating after an unintended time interval.




Figure 9.58 – DelayedFunction

9.4.2 Methods::FMEA::FMEAProfile

FMEAItem

Package: FMEAProfile

isAbstract: No

Generalization: Block
Extension: Class

Description

See [AbstractFMEAItem](#) library class for the definition of a FMEA Item concept.




Figure 9.59 – FMEAItem

Constraints

```

[1] -- FMEAItem stereotype can only be applied on any class, specialized from
FMEAItemIsAbstractFMEAItem AbstractFMEAItem from FMEA Library
self.base_Class->asSet()->closure(general).name->includes('AbstractFMEAItem')
  
```

9.5 Methods::FTA

Fault Tree Analysis (FTA) is a top-down failure analysis in which an undesired state of a system is analyzed using Boolean logic to combine a series of lower-level (basic) events. This analysis method is used to understand how systems can fail, to identify the best ways to reduce risk and to determine event rates of a safety accident or a functional failure.

The FTA package contains all required elements to implement this analysis. Support for Fault Tree Analysis (FTA) modeling is based on the IEC 61025:2006 standard. Using this standard ensures that the specification offers a form of FTA that is based on best practices and accepted by practitioners. It is also possible for a user to extend the capabilities of the FTA package to enable, for example, dynamic fault tree analysis and component fault tree modeling while still remaining compatible with other information modeled using the specification.

In order to combine FMEA and FTA analysis, a connection between a failure mode and a fault tree event needs to be made. Therefore, the Cause of an FMEAItem can be interpreted as the event which leads to a failure of a system item. By combining FMEAs and FTAs, both analyses can be used to verify the analysis results. This may lead to a better understanding of the behavior of a system during erroneous behavior.

9.5.1 Methods::FTA::FTALibrary

FTAElement

Package: FTALibrary

isAbstract: Yes

Generalization: [DysfunctionalEvent](#)

Applied Stereotype: «Situation»

Description

Any of the [Events](#) and [Gates](#) needed for the evaluation of the [TopEvent](#) probability.




Figure 9.60 – FTAElement

Attributes

probability : Real, redefines [likelihood](#)

The probability that the event represented by the owning FTA element occurs. Probability is a Real value between 0 and 1.

source Gate : Gate (member end of input association)

FTATree

Package: FTALibrary

isAbstract: No

Generalization: [FTAElement](#), [Scenario](#)

Applied Stereotype: «Tree»

Description

A collection of FTAElements and their interrelationships for the evaluation of the top event probability.




Figure 9.61 – FTATree

Attributes

topEvent : Event[1] (member end of association)

Undesired event which lead to the failure of the system.

Methods: FTA::FTALibrary::Events

Package of events for building fault trees.

Event

Package: Events

isAbstract: Yes

Generalization: [FTAElement](#)

Applied Stereotype: «Situation»

Description

The Event is a base class for all types of fault tree events. It is a kind of [DysfunctionalEvent](#).




Figure 9.62 – Event

Attributes

priority : Integer[0..1]

The priority field is only used to indicate the order of this event when multiple events are inputs of Priority AND ([SEQ](#)) gate.

target Gate : Gate (member end of output association)

BasicEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: [«BasicEvent»](#)

Description

A basic initiating failure requiring no further development.




Figure 9.63 – BasicEvent

IntermediateEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: [«IntermediateEvent»](#)

Description

An intermediate event is a failure which occurs because of one or more antecedent events acting through logic gates.




Figure 9.64 – IntermediateEvent

Attributes

probability : Real, redefines [probability](#)

Probability of the intermediate event is derived. It is calculated by the gate from the probabilities of the more basic events.

TopEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: «TopEvent»

Description

Undesired event - failure or effect - at the top of the fault tree.




Figure 9.65 – TopEvent

Attributes

probability : Real, redefines [probability](#)

The (derived) probability of the top event is the result of the fault tree calculation.

ConditionalEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: «ConditionalEvent»

Description

Specific conditions or restrictions that apply to any logic gate (used primarily with PRIORITY AND and INHIBIT gates).




Figure 9.66 – ConditionalEvent

DormantEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: [«DormantEvent»](#)

Description

The dormant event is similar to [BasicEvent](#) but indicates the latent failure which is discovered by periodical tests.




Figure 9.67 – DormantEvent

UndevelopedEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: [«BasicEvent»](#), [«Undeveloped»](#)

Description

An event which is not further developed either because it is of insufficient consequence or because information is unavailable.




Figure 9.68 – UndevelopedEvent

HouseEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: [«HouseEvent»](#)

Description

An event which can be set to occur or not occur.




Figure 9.69 – HouseEvent

Attributes

probability : HouseEventProbability, Probability of the house event is 0 or 1. It is set before doing a fault tree evaluation, redefines [probability](#)

ZeroEvent

Package: Events

isAbstract: No

Generalization: [Event](#)

Applied Stereotype: «ZeroEvent»

Description

An event which represents a condition or an event that will never occur.




Figure 9.70 – ZeroEvent

Attributes

probability : Real, redefines [probability](#) The probability of zero event is always 0.

Methods::FTA::FTALibrary::Gates

Package of logical conditions for building fault trees.

Gate

Package: Gates

isAbstract: Yes

Applied Stereotype: «Situation»

Description

An [FTAElement](#) that combines input [Event](#) probabilities in a prescribed manner to determine output [Event](#) probability. The output event occurs if the combination of input events is satisfied. The gate subtypes specify the necessary combination.




Figure 9.71 – Gate

Attributes

source Event : Event[0..*] (member end of input association)

target Event : Event[1] (member end of output association)

AND

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», «AND»

Description

The output event occurs only if all input events occur.




Figure 9.72 – AND

OR

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», «OR»

Description

The output event occurs if at least one of input event occurs.




Figure 9.73 – OR

NOT

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», [«NOT»](#)

Description

The output event occurs if the input event does not occur.




Figure 9.74 – NOT

XOR

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», [«XOR»](#)

Description

The output event occurs if exactly one of the input events occurs.




Figure 9.75 – XOR

SEQ

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», «SEQ»

Description

The output event occurs if all the input events occur in a specific sequence.




Figure 9.76 – SEQ

INHIBIT

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «INHIBIT», «Block»

Description

The output event occurs if the (single) input event occurs in the presence of an enabling condition.




Figure 9.77 – INHIBIT

Attributes

condition : Event[0..*] (member end of condition association)

MAJORITY_VOTE

Package: Gates

isAbstract: No

Generalization: [Gate](#)

Applied Stereotype: «Block», «MAJORITY_VOTE»

Description

The output event occurs if the majority of the input events occurs. It has a threshold parameter m.




Figure 9.78 – MAJORITY_VOTE

Attributes

m : Integer

The m parameter defines the number of input events that form a majority. It is not necessarily $\text{ceil}(\text{number_of_inputs} / 2)$. It is possible to stipulate that e.g., 5 (or 2) input events have to occur out of total of 7 events for majority gate to fire.

Methods::FTA::FTALibrary::Gates::ConstraintBlocks

Reference implementation for the FTA gates.

ANDConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [AND](#) gate.

Attributes

output :

input : [0..*]

Constraints

- [1] Probability of AND node is simply a multiplication of probabilities of incoming nodes.
Note - this simplistic calculation assumes that incoming node events are mutually independent.

ORConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [OR](#) gate.

Attributes

output :

input : [0..*]

Constraints

- [1] Probability of OR node is calculated as opposite probability of the event where neither of the input events happen.
This follows De Morgan's theorem - $OR(input1, input2, input3...) = NOT\ AND\ (NOT\ input1, NOT\ input2, NOT\ input3...)$.
Note - this simplistic calculation assumes that incoming node events are mutually independent.

SEQConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [SEQ](#) gate.

Attributes

output :

input : Real[0..*]

Constraints

- [1] Probability of SEQ node is calculated the same way as AND node - it is simply a multiplication of probabilities of incoming nodes.

This simplistic calculation cannot capture time-dependency of the events; only more complex simulations can estimate this probability.

XORConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [XOR](#) gate.

Attributes

output :

input : [0..*]

Constraints

[1]

In case of two inputs, XOR probability is calculated by ORing of two event combination probabilities - probability that first event happened and second did not ORed with probability that second event happened while first did not.

$$\text{Input1 XOR Input2} = \text{Input1 AND NOT Input2 OR Input2 AND NOT Input1}$$

Since combinations are mutually exclusive, simple (+) operation can be used for ORing them. Therefore

$$\text{Input1 XOR Input2} = \text{Input1 AND NOT Input2} + \text{Input2 AND NOT Input1}$$

Further expanding ANDs and NOTs using their corresponding formulas, we get

$$\text{Input1 XOR Input2} = \text{Input1} * (1 - \text{Input2}) + \text{Input2} * (1 - \text{Input1}) = \text{Input1} + \text{Input2} - 2 * \text{Input1} * \text{Input2}$$

This formula can be iteratively applied for the case with number of inputs greater than two.

Note - this simplistic calculation assumes that incoming node events are mutually independent.

INHIBITConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [INHIBIT](#) gate.

Attributes

output :

input : [0..*]

condition : Real

Constraints

[1]

Probability of INHIBIT node is calculated the same way as AND node - it is simply a multiplication of probabilities of input nodes and condition nodes.

Note - this simplistic calculation assumes that incoming node events and conditions are mutually independent.

MAJORITY_VOTEConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [MAJORITY_VOTE](#) gate.

Attributes

output :

input : [0..*]

m :

Constraints

[1]

Majority Vote probability can be calculated by iteratively examining all the combinations of input events, taking those combinations that satisfy the condition that at least m input events happen, then calculating probability of each combination using AND formula (multiplying all individual event probabilities in that combination) and then calculating cumulative probability of all combinations by ORing them.

Note - this simplistic calculation assumes that incoming node events are mutually independent.

NOTConstraintBlock

Package: ConstraintBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Reference implementation for the [NOT](#) gate.

Attributes

output :

input : [1]

Constraints

[1]

Probability of NOT node is calculated as probability of the event opposite to the input event.

Thereby it is unity minus probability of input event.

9.5.2 Methods::FTA::FTAProfile

Tree

Package: FTAProfile

isAbstract: No

Generalization: [Situation](#)

Extension: Class

Description

A marker stereotype for fault trees. See [FTATree](#) library class for definition.




Figure 9.79 – Tree

Constraints

[1] TreeIsFTATree -- Tree stereotype can only be applied on any class specialized from FTATree from FTA Library
self.base_Class->asSet()->closure(general).name->includes('FTATree')

Gate

Package: FTAProfile
isAbstract: Yes
Extension: Class, Property

Description

A marker stereotype for fault tree gates. See [Gate](#) library class for definition.




Figure 9.80 – Gate

Event

Package: FTAProfile
isAbstract: Yes
Extension: Class, Property

Description

A marker stereotype for fault tree events. See [Event](#) library class for definition.

If the Event stereotype is applied to a class, then that class also must have the Situation stereotype (or its descendants) applied.




Figure 9.81 – Event

DormantEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for dormant events. See [DormantEvent](#) library class for definition.




Figure 9.82 – DormantEvent

Constraints

```
[1]
DormantEventIsDormantEvent
    if not self.base_Class->isEmpty() then
        --DormantEvent stereotype can only be applied on any class specialized from
        DormantEvent from FTA Library
        self.base_Class->asSet()->closure(general).name->includes('DormantEvent')
    else
        --DormantEvent stereotype can only be applied on any property whose type is
        specialized from DormantEvent from FTA Library
        self.base_Property.type->asSet()->closure(general).name->includes('DormantEvent')
    endif
```

BasicEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for basic events. See [BasicEvent](#) library class for definition.




Figure 9.83 – BasicEvent

Constraints

[1] BasicEventIsBasicEvent

```
if not self.base_Class->isEmpty() then
  --BasicEvent stereotype can only be applied on any class specialized from
  BasicEvent from FTA Library
  self.base_Class->asSet()->closure(general).name->includes('BasicEvent')
else
  --BasicEvent stereotype can only be applied on any property whose type is
  specialized from BasicEvent from FTA Library
  self.base_Property.type->asSet()->closure(general).name-
  >includes('BasicEvent')
endif
```

[2] UndevelopedEventIsUndevelopedEvent

```
--BasicEvent + Undeveloped stereotype combination can be applied on any
class specialized from UndevelopedEvent from FTA Library
Undeveloped.allInstances().base_Element->includesAll(self.base_Class)
implies
self.base_Class->asSet()->closure(general).name-
>includes('UndevelopedEvent')
```

ConditionalEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for conditional events. See [ConditionalEvent](#) library class for definition.




Figure 9.84 – ConditionalEvent

Constraints

```
[1]
ConditionalEventIsConditionalEvent
    if not self.base_Class->isEmpty() then
        --ConditionalEvent stereotype can only be applied on any class specialized
        from ConditionalEvent from FTA Library
        self.base_Class->asSet()->closure(general).name-
        >includes('ConditionalEvent')
    else
        --ConditionalEvent stereotype can only be applied on any property whose type
        is specialized from ConditionalEvent from FTA Library
        self.base_Property.type->asSet()->closure(general).name-
        >includes('ConditionalEvent')
    endif
```

ZeroEvent

Package: FTAProfile
isAbstract: No
Generalization: [Event](#)
Extension: Class, Property

Description

A marker stereotype, carrying icon for zero events. See [ZeroEvent](#) library class for definition.




Figure 9.85 – ZeroEvent

Constraints

[1] ZeroEventIsZeroEvent

```
if not self.base_Class->isEmpty() then
  --ZeroEvent stereotype can only be applied on any class specialized from ZeroEvent
  from FTA Library
  self.base_Class->asSet()->closure(general).name->includes('ZeroEvent')
else
  --ZeroEvent stereotype can only be applied on any property whose type is
  specialized from ZeroEvent from FTA Library
  self.base_Property.type->asSet()->closure(general).name->includes('ZeroEvent')
endif
```

HouseEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for house events. See [HouseEvent](#) library class for definition.




Figure 9.86 – HouseEvent

Constraints

[1] HouseEventIsHouseEvent

```
if not self.base_Class->isEmpty() then
  --HouseEvent stereotype can only be applied on any class specialized from
  HouseEvent from FTA Library
  self.base_Class->asSet()->closure(general).name->includes('HouseEvent')
else
  --HouseEvent stereotype can only be applied on any property whose type is
  specialized from HouseEvent from FTA Library
  self.base_Property.type->asSet()->closure(general).name->includes('HouseEvent')
endif
```

AND

Package: FTAProfile
isAbstract: No
Generalization: [Gate](#)
Extension: Class, Property

Description

A marker stereotype, carrying icon for AND gates. See [AND](#) library class for definition.




Figure 9.87 – AND

Constraints

[1] ANDIsAND

```
if not self.base_Class->isEmpty() then
    --AND stereotype can only be applied on any class specialized from AND gate from
    FTA Library
    self.base_Class->asSet()->closure(general).name->includes('AND')
else
    --AND stereotype can only be applied on any property whose type is specialized
    from AND from FTA Library
    self.base_Property.type->asSet()->closure(general).name->includes('AND')
endif
```

OR

Package: FTAProfile
isAbstract: No
Generalization: [Gate](#)
Extension: Class, Property

Description

A marker stereotype, carrying icon for OR gates. See [OR](#) library class for definition.




Figure 9.88 – OR

Constraints

[1] ORIsOR

```

if not self.base_Class->isEmpty() then
    --OR stereotype can only be applied on any class specialized from OR gate from
    FTA Library
    self.base_Class->asSet()->closure(general).name->includes('OR')
else
    --OR stereotype can only be applied on any property whose type is specialized from
    OR from FTA Library
    self.base_Property.type->asSet()->closure(general).name->includes('OR')
endif

```

SEQ

Package: FTAProfile

isAbstract: No

Generalization: [Gate](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for SEQ gates. See [SEQ](#) library class for definition.




Figure 9.89 – SEQ

Constraints

[1] SEQIsSEQ

```

if not self.base_Class->isEmpty() then
    --SEQ stereotype can only be applied on any class specialized from SEQ gate from
    FTA Library
    self.base_Class->asSet()->closure(general).name->includes('SEQ')
else
    --SEQ stereotype can only be applied on any property whose type is specialized
    from SEQ from FTA Library
    self.base_Property.type->asSet()->closure(general).name->includes('SEQ')
endif

```

XOR

Package: FTAProfile

isAbstract: No

Generalization: [Gate](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for XOR gates. See [XOR](#) library class for definition.




Figure 9.90 – XOR

Constraints

[1] XORIsXOR

```

if not self.base_Class->isEmpty() then
    --XOR stereotype can only be applied on any class specialized from XOR gate from
    FTA Library
    self.base_Class->asSet()->closure(general).name->includes('XOR')
else
    --XOR stereotype can only be applied on any property whose type is specialized
    from XOR from FTA Library
    self.base_Property.type->asSet()->closure(general).name->includes('XOR')
endif

```

INHIBIT

Package: FTAProfile

isAbstract: No

Generalization: [Gate](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for INHIBIT gates. See [INHIBIT](#) library class for definition.




Figure 9.91 – INHIBIT

Constraints

```
[1] INHIBITIsINHIBIT    if not self.base_Class->isEmpty() then
                        --INHIBIT stereotype can only be applied on any class specialized from INHIBIT
                        gate from FTA Library
                        self.base_Class->asSet()->closure(general).name->includes('INHIBIT')
                        else
                        --INHIBIT stereotype can only be applied on any property whose type is specialized
                        from INHIBIT from FTA Library
                        self.base_Property.type->asSet()->closure(general).name->includes('INHIBIT')
                        endif
```

MAJORITY_VOTE

Package: FTAProfile

isAbstract: No

Generalization: [Gate](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for MAJORITY_VOTE gates. See [MAJORITY_VOTE](#) library class for definition.




Figure 9.92 – MAJORITY_VOTE

Constraints

```
[1]
MAJORITY_VOTE is MAJORITY_VOTE
    if not self.base_Class->isEmpty() then
        --MAJORITY_VOTE stereotype can only be applied on any class
        specialized from MAJORITY_VOTE gate from FTA Library
        self.base_Class->asSet()->closure(general).name-
        >includes('MAJORITY_VOTE')
    else
        --MAJORITY_VOTE stereotype can only be applied on any property
        whose type is specialized from MAJORITY_VOTE from FTA Library
        self.base_Property.type->asSet()->closure(general).name-
        >includes('MAJORITY_VOTE')
    endif
```

NOT

Package: FTAProfile

isAbstract: No

Generalization: [Gate](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for NOT gates. See [NOT](#) library class for definition.




Figure 9.93 – NOT

Constraints

[1] NOTIsNOT

```
if not self.base_Class->isEmpty() then
  --NOT stereotype can only be applied on any class specialized from NOT gate from
  FTA Library
  self.base_Class->asSet()->closure(general).name->includes('NOT')
else
  --NOT stereotype can only be applied on any property whose type is specialized
  from NOT from FTA Library
  self.base_Property.type->asSet()->closure(general).name->includes('NOT')
endif
```

IntermediateEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for intermediate events. See [IntermediateEvent](#) library class for definition.




Figure 9.94 – IntermediateEvent

Constraints

[1]

IntermediateEventIsIntermediateEvent

```
if not self.base_Class->isEmpty() then
  --IntermediateEvent stereotype can only be applied on any class specialized
  from IntermediateEvent from FTA Library
  self.base_Class->asSet()->closure(general).name-
  >includes('IntermediateEvent')
else
  --IntermediateEvent stereotype can only be applied on any property whose
  type is specialized from IntermediateEvent from FTA Library
  self.base_Property.type->asSet()->closure(general).name-
  >includes('IntermediateEvent')
endif
```

TopEvent

Package: FTAProfile

isAbstract: No

Generalization: [Event](#)

Extension: Class, Property

Description

A marker stereotype, carrying icon for top events. See [TopEvent](#) library class for definition.




Figure 9.95 – TopEvent

Constraints

```
[1] TopEventIsTopEvent    if not self.base_Class->isEmpty() then
                           --TopEvent stereotype can only be applied on any class specialized from TopEvent
                           from FTA Library
                           self.base_Class->asSet()->closure(general).name->includes('TopEvent')
                           else
                           --TopEvent stereotype can only be applied on any property whose type is specialized
                           from TopEvent from FTA Library
                           self.base_Property.type->asSet()->closure(general).name->includes('TopEvent')
                           endif
```

TransferIn

Package: FTAProfile

isAbstract: No

Extension: Property

Description

The node of the current fault tree that indicates that the tree is developed further as a separate fault tree - [TransferOut](#).



Figure 9.96 – TransferIn

Constraints

```
[1] TypeIsTransferOut -- type of TransferIn property must be TransferOut FTA Tree
TransferOut.allInstances().base_Class->includesAll(self.base_Property.type)
```

TransferOut

Package: FTAProfile

isAbstract: No

Generalization: [Tree](#)

Extension: Class

Description

A marker stereotype for partial fault trees. It indicates that this tree is used as a part of another fault tree through [TransferIn](#). The computed probability of the top event of the TransferOut tree is used as a probability of the [TransferIn](#) node.




Figure 9.97 – TransferOut

9.6 Methods::STPA

The System Theoretical Process Analysis (STPA) is a hazard analysis technique based on control and system theory. In comparison, most existing hazard analysis techniques are based on reliability theory. In STPA, however, the easy goals are pursued as in any hazard analysis, i.e., collecting information on how hazards may occur. For further information on this approach the handbook¹ describes the method and show the application.

9.6.1 Methods::STPA::STPA Library

OutOfSequence

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: [«UndesiredControlAction»](#)

Description

STPA Guideword, describing kind of control.

Commented [AA19]: RAAML11-28

Deleted: [UnsafeControlAction](#)

Commented [AA20]: RAAML11-28

Deleted: [safe](#)

¹ https://psas.scripts.mit.edu/home/get_file.php?name=STPA_handbook.pdf




Figure 9.98 – OutOfSequence

Late

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: «UndesiredControlAction»

Description

STPA Guideword, describing kind of control.




Figure 9.99 – Late

Early

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: «UndesiredControlAction»

Description

STPA Guideword, describing kind of control.




Figure 9.100 – Early

TooLong

Package: STPA Library

isAbstract: Yes


Generalization: [UndesiredControlAction](#)

Applied Stereotype: «UndesiredControlAction»

Description

STPA Guideword, describing kind of control.

Commented [AA21]: RAAML11-28




Deleted:

Deleted: [safe](#)

Commented [AA22]: RAAML11-28

Deleted: [safe](#)

Commented [AA23]: RAAML11-28




Deleted:

Deleted: [safe](#)

Commented [AA24]: RAAML11-28

Deleted: [safe](#)

Commented [AA25]: RAAML11-28



Deleted:

Deleted: [safe](#)

Commented [AA26]: RAAML11-28

Deleted: [safe](#)




Figure 9.101 – TooLong

TooShort

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: [«UndesiredControlAction»](#)

Description

STPA Guideword, describing kind of control.




Figure 9.102 – TooShort

Provided

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: [«UndesiredControlAction»](#)

Description

STPA Guideword, describing a kind of control.




Figure 9.103 – Provided

NotProvided


Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredControlAction](#)

Applied Stereotype: [«UndesiredControlAction»](#)

Commented [AA27]: RAAML11-28




Deleted:

Deleted: [safe](#)

Commented [AA28]: RAAML11-28

Deleted: [safe](#)

Commented [AA29]: RAAML11-28




Deleted:

Deleted: [safe](#)

Commented [AA30]: RAAML11-28

Deleted: [safe](#)

Commented [AA31]: RAAML11-28



Deleted:

Deleted: [safe](#)

Commented [AA32]: RAAML11-28

Deleted: [safe](#)

Description

STPA Guideword, describing kind of control.




Figure 9.104 – NotProvided

LossScenario

Package: STPA Library

isAbstract: Yes

Generalization: [Scenario](#)

Applied Stereotype: [«LossScenario»](#)

Description

A sequence of situations starting from [causal](#) Factors, that (through Process Model deficiencies) leads to an [UndesiredControlAction](#) (which further leads to risks and possibly losses).




Figure 9.105 – LossScenario

Attributes


[causal](#)Factor : Factor[0..*] (member end of association, subsets [scenarioStep](#))

A causalFactor can be used to further refine Process Model inadequacies - specifying causes of deficiencies in the process model and/or other contributing factors. Undesired control action related to the loss scenario.

[undesiredControlAction](#) :

[UndesiredControlAction](#)[0..*] (member end of association, subsets [scenarioStep](#))


Commented [AA33]: RAAML11-28



Deleted:

Deleted: UnsafeControlAction

Commented [AA34]: RAAML11-28



Deleted:

Formatted: Font: (Default) Times New Roman

Deleted: unsafeControlAction

Deleted: UnsafeControlAction

Commented [AA35]: RAAML11-28

processModelFlaw : ProcessModelFlaw[0..*]
(member end of association, subsets scenarioStep)

Commented [AA36]: RAAML11-28

ProcessModelFlaw

Commented [AA37]: RAAML11-28

Package: STPA Library

isAbstract: No

Applied Stereotype: «Situation»

Description

A ProcessModelFlaw describes a process / control loop model that may lead to an Undesired Control Action. The four high level kinds of process model deficiencies can be used to specify the section of the control loop.

Commented [AA38]: RAAML11-28

Process model deficiencies are often called (high level) Scenario in STPA theory.

Deleted: Unsafe

Commented [AA39]: RAAML11-28




Figure 9.106 – ProcessModelFlaw

Attributes

undesiredControlAction : Undesired control action related to process model flaw.
UndesiredControlAction[0..*] (member end of ProcessModelFlawConsequence association, redefines to)

Commented [AA40]: RAAML11-28

Deleted: Factor : Factor[0..*] (member end of ProcessModelFactor association, redefines from)

Formatted: Font: (Default) Times New Roman

Formatted Table

Deleted: UnsafeControlAction

InadequateControllerDecisions

Package: STPA Library

isAbstract: Yes

Generalization: ProcessModelFlaw

Applied Stereotype: «Situation»

Commented [AA41]: RAAML11-28

Description

A kind of ProcessFlaw.





Figure 9.107 – InadequateControllerDecisions



InadequateControlExecution

Package: STPA Library
 isAbstract: Yes
 Generalization: [ProcessModelFlaw](#)
 Applied Stereotype: «Situation»

Description
 A kind of ProcessFlaw.

Commented [AA43]: RAAML11-28




Figure 9.108 – InadequateControlExecution



InadequateProcessBehavior

Package: STPA Library
 isAbstract: Yes
 Generalization: [ProcessModelFlaw](#)
 Applied Stereotype: «Situation»

Description
 A kind of ProcessFlaw.

Commented [AA45]: RAAML11-28





Figure 9.109 – InadequateProcessBehavior



InadequateFeedbackAndInputs

Package: STPA Library

isAbstract: Yes

Generalization: [ProcessModelFlaw](#)

Applied Stereotype: «Situation»

Description

A kind of ProcessFlaw.




Figure 9.110 – InadequateFeedbackAndInputs

[UndesiredControlAction](#)

Package: STPA Library

isAbstract: Yes

Generalization: [UndesiredState](#)

Applied Stereotype: «UndesiredControlAction»

Description


An **Undesired** Control Action (UCA), used in STPA, describes in what context providing / not providing a Control Action might lead to an undesired result.

A UCA generally consist of four parts:

- Controller (Subject) that issues the Control Action - inferred from Control Action and model of the system (block/part producing the control action).
- Guideword (provides, does not provide, etc.) - indicated using Generalization relationship
- Control Action - connected with RelevantTo relationship.
- Context in which Control Action leads to undesired outcome - sub situation of (part of) UCA situation.

Commented [AA47]: RAAML11-28

Commented [AA48]: RAAML11-28



Deleted:

Commented [AA49]: RAAML11-28

Deleted: UnsafeControlAction

Commented [AA50]: RAAML11-28

Deleted: [UnsafeControlAction](#)

Commented [AA51]: RAAML11-28

Deleted: Unsafe

Formatted




Figure 9.111 – UndesiredControlAction

Attributes

Context : AbstractOperationalSituation[1] [The context of the undesired control action.](#)
(member end of association)

processModelFlaw : [Process model flaw related to the undesired control action.](#)
ProcessModelFlaw[0..*] (member end of [ProcessModelFlawConsequence](#) association, redefines [from](#))

harmPotential : HarmPotential[0..*] [Harm potential related to the undesired control action.](#)
(member end of [UndesiredControlActionHarmPotential](#) association, redefines [to](#))


RiskRealization

Package: STPA Library
isAbstract: No
Generalization: [AbstractRisk](#), [Causality](#)
Applied Stereotype: «Block»

Description

Association between the Loss and Hazard (potential harm).

Commented [AA52]: RAAML11-28



Deleted:

Commented [AA53]: RAAML11-28

Deleted: safe

Formatted: Font: (Default) Times New Roman

Deleted: [UnsafeControlActionHarmPotential](#)

Commented [AA54]: RAAML11-28

Moved up [1]: Factor¶

Deleted: **Package:** STPA Library¶
isAbstract: No¶
Generalization: [AbstractCause](#)¶
Applied Stereotype: «Situation»¶
¶
Description¶
A Factor (F) can be used to further refine Process Model inadequacies - specifying causes of deficiencies in the process model and/or other contributing factors.¶
¶
Attributes¶
processModel : ProcessModel[0..*] (member end of [ProcessModelFactor](#) association, redefines [to](#))

Formatted: Font: (Default) Times New Roman




Figure 9.112 – RiskRealization

ProcessModelFlawFactor

Package: STPA Library

Generalization: Causality

Description

Causal relationship between CausalFactor and ProcessFlaw




Figure 9.113 – ProcessModelFlawFactor

Association ends

processModelFlaw : Process model flaw related to the process model flaw factor.

ProcessModelFlaw[0..*] (member end

of ProcessModelFlawFactor

association, redefines to)

causalFactor : Factor[0..*] (member end

of ProcessModelFlawFactor

association, redefines from)

A causalFactor can be used to further refine Process Model inadequacies - specifying causes of deficiencies in the process model and/or other contributing factors.

ProcessModelFawConsequence

Package: STPA Library

Generalization: Causality

Description

Causal relationship between ProcessModelFlaw and UndesiredControlAction

Commented [AA55]: RAAML11-28

Commented [AA56]: RAAML11-28

Commented [AA57]: RAAML11-28

Commented [AA58]: RAAML11-28

Commented [AA59]: RAAML11-28

Formatted: Font: (Default) Times New Roman

Formatted: Font: (Default) Times New Roman

Commented [AA60]: RAAML11-28

Commented [AA61]: RAAML11-28

Deleted: UnsafeControlAction




Figure 9.114 – ProcessModelFlawConsequence

Association ends

UndesiredControlAction : Undesired control action related to process model flow.

UndesiredControlAction[0..*] (member end of ProcessModelFlawConsequence association, redefines to)

processModelFlaw : Process model flow related to the undesired control action.
processModelFlaw : ProcessModelFlaw[0..*] (member end of ProcessModelFlawConsequence association, redefines from)

UndesiredControlActionHarmPotential

Package: STPA Library
 Generalization: Causality

Description

Causal relationship between UndesiredControlAction and HarmPotential.




Figure 9.115 – UndesiredControlActionHarmPotential

Association ends

harmPotential : Harm potential related to the undesired control action.

harmPotential : HarmPotential[0..*] (member end of UndesiredControlActionHarmPotential association, redefines to)

undesiredControlAction : Harm potential (or hazard, or threat) related to the undesired control action.

UndesiredControlAction[0..*] (member end of UndesiredControlActionHarmPotential association, redefines from)

Commented [AA62]: RAAML11-28

Commented [AA63]: RAAML11-28

Deleted: unsafeControlAction

Formatted: Font: (Default) Times New Roman

Deleted: UnsafeControlAction

Commented [AA64]: RAAML11-28

Formatted: Font: (Default) Times New Roman

Commented [AA65]: RAAML11-28

Deleted: safe

Commented [AA66]: RAAML11-28

Deleted: UnsafeControlAction

Deleted: RiskSource

Commented [AA67]: RAAML11-28

Deleted: UnsafeControlActionHarmPotential

Deleted: unsafeControlAction

Formatted: Font: (Default) Times New Roman

Commented [AA68]: RAAML11-28

Deleted: UnsafeControlAction

Deleted: UnsafeControlActionHarmPotential

9.6.2 Methods::STPA::STPA Profile

ControlAction
Package: STPA Profile
isAbstract: No
Extension: Signal, Class, DataType

Description
A Control Action (CA) is an output signal from a functional / logical Controller to a ControlledProcess (via the Actuator), that determines the receiving process behaviour.




Figure 9.116 – ControlAction

Feedback
Package: STPA Profile
isAbstract: No
Extension: Signal, Class, DataType

Description
A Feedback is an input signal to a functional / logical Controller from a ControlledProcess (via the Sensor), that characterizes the current processes behavior (or the environment).




Figure 9.117 – Feedback

UndesiredControlAction
Package: STPA Profile
isAbstract: No
Generalization: [Situation](#)
Extension: Class

Description
Stereotype used to demarcate all the UndesiredControlActions.

Commented [AA69]: RAAML11-28
Deleted: UnsafeControlAction

Commented [AA70]: RAAML11-28
Deleted: UnsafeControlActions




Figure 9.118 – ~~UndesiredControlAction~~

~~UnsafeControlAction~~

Package: STPA Profile


isAbstract: No

Generalization: ~~UndesiredControlAction~~

Extension: Class

Description

Stereotype used to demarcate all the ~~UnsafeControlActions~~.



Deleted:

Commented [AA71]: RAAML11-28

Deleted: safe

Commented [AA72]: RAAML11-28

Formatted: Font: Not Bold

Commented [AA73]: RAAML11-28




Figure 9.119 – ~~UnsafeControlAction~~

ControlledProcess

Package: STPA Profile

isAbstract: No

Extension: Property, Class

Description

An abstract representation of the system and its behaviours that need to be supervised and governed.

Controller is controlling this process through the ControlAction via the Actuator.




Figure 9.120 – ControlledProcess

Commented [AA74]: RAAML11-28

Commented [AA75]: RAAML11-28

Actuator

Package: STPA Profile

isAbstract: No

Extension: Property, Class

Description

Actuator receives ControlActions from Controller and influences the ControlledProcess in some way.




Figure 9.121 – Actuator

Sensor

Package: STPA Profile

isAbstract: No

Extension: Property, Class

Description

Sensor assesses the ControlledProcess (also environment or other controllers) and gives Feedback to the Controller.




Figure 9.122 – Sensor

Controller

Package: STPA Profile

isAbstract: No

Extension: Property, Class

Description

Controller sends the ControlActions and receives Feedback.




Figure 9.123 – Controller

ControlStructure

Package: STPA Profile

isAbstract: No
Generalization: Block
Extension: Class

Description

ControlStructure is a system-of-systems composed of ControlledProcess, Controller and their functional relationships - ControllActions, Feedbacks, describing feedback control loops.




Figure 9.124 – ControlStructure

LossScenario

Package: STPA Profile
isAbstract: No
Generalization: [Situation](#)
Extension: Class

Description

Stereotype used to demarcate all the LossScenarios.




Figure 9.125 – LossScenario

9.7 GSN

The GSN profile is an implementation of the core notation described in the GSN version 2 standard. The GSN standard is made available under creative commons licence version 4:

“To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/> or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.”.

The OMG acknowledges the work of the SCSC ACWG in the production of the GSN standard.

Whilst GSN is an extension of the OMG SACM standard, which has a defined meta-model based on the OMG MOF standard, the objectives of RAAML to integrate with SysML 1.6 necessitate the use of a UML profile interpretation of the GSN standard.

9.7.1 GSN::GSN Profile

Notation

Most of the stereotypes in GSN profile have stereotype images specified. Displaying the stereotyped GSN elements in UML Class diagram may follow the UML standard prescription (UML 2.5.1, Chapter 12.3.4.1 Icon presentation) for displaying elements having stereotypes with icons, namely:

- Showing model element as an image with element name below
- Showing model element as a box with the iconic form image inside the box at the top left



Figure 9.126 – Standard UML notation for stereotyped elements (from UML 2.5.1, Figure 12.25)

However, in addition to the notation described in UML standard, this standard allows additional notation. Namely – using stereotype image as a (resizable) outline/shape of the box, with the same compartments that are prescribed by the UML standard (including name/stereotype/tag values compartment) inside. This notation is recommended i.e., preferred over the standard UML notation.

An example of the SCSC/GSN standard representation of the GSN extension is shown in Figure 9.106. See the SCSC/GSN standard for the shapes and text placement to be used for various model element types.



Figure 9.127 - Strategy notation

Combined Stereotype Notation

The UML standard allows a combination of several stereotypes applied on the model element. Namely – the combination of Goal+Undeveloped stereotypes and Strategy+Undeveloped stereotypes is being used. An example of this notation is depicted in Figure 9.107. See the SCSC/GSN standard for the shapes and text placement to be used for various model element types.



Figure 9.128 - Combined notation

GSNNode

Package: GSN Profile

isAbstract: Yes

Extension: Element

Description

Root type for all the different kinds of nodes in GSN.

Note: name versus human-readable ID

GSN domain elements frequently have both a short phrase, describing the element and human-readable identifier. For example:

G1 Control System is acceptably safe to operate

In this example “Control System is acceptably safe to operate” is a short phrase, describing the goal, while G1 is a human-readable identifier of the goal.

In this standard, the short phrase shall be captured as UML model element name – NamedElement::name field. Human-readable identifier shall be stored in a separate tag, defined in the Core profile – IDCarrier::id..




Figure 9.129 – GSNNode

Attributes

id : String[0..1]

GSNArgumentNode

Package: GSN Profile

isAbstract: Yes

Generalization: [GSNNode](#)

Extension: Element

Description

A [Goal](#) or a [Strategy](#).




Figure 9.130 – GSNArgumentNode

Solution

Package: GSN Profile
isAbstract: No
Generalization: [GSNNode](#)
Extension: Class

Description

A solution presents a reference to an evidence item or items.




Figure 9.131 – Solution

Goal

Package: GSN Profile
isAbstract: No
Generalization: [GSNArgumentNode](#)
Extension: Class

Description

A goal presents a claim forming part of the argument.




Figure 9.132 – Goal

Strategy

Package: GSN Profile
isAbstract: No
Generalization: [GSNArgumentNode](#)
Extension: Class

Description

A strategy describes the nature of the inference that exists between a goal and its supporting goal(s).




Figure 9.133 – Strategy

ContextualInformation

Package: GSN Profile

isAbstract: Yes

Extension: Element

Description

A [Context](#) or an [Assumption](#) or a [Justification](#).




Figure 9.134 – ContextualInformation

Attributes

id : String[0..1]

Context

Package: GSN Profile

isAbstract: No

Generalization: [ContextualInformation](#)

Extension: Class

Description

A context presents a contextual artefact. This can be a reference to contextual information, or a statement.




Figure 9.135 – ContextStatement

Assumption

Package: GSN Profile

isAbstract: No

Generalization: [SupportingInformation](#)

Extension: Class

Description

An assumption presents an intentionally unsubstantiated statement.




Figure 9.136 – Assumption

Justification

Package: GSN Profile

isAbstract: No

Generalization: [ContextualInformation](#)

Extension: Class

Description

A justification presents a statement of rationale.




Figure 9.137 – Justification

InContextOf

Package: GSN Profile

isAbstract: No

Extension: Dependency

Description

InContextOf declares a contextual relationship.

Permitted connections are: goal-to-context, goal-to-assumption, goal-to-justification, strategy-to-context, strategy-to-assumption and strategy-to-justification.




Figure 9.138 – InContextOf

Constraints

- | | |
|--------------------------|---|
| [1] ClientIsArgumentNode | -- client of InContextOf must be GSNAArgumentNode
GSNAArgumentNode.allInstances().base_Element->includesAll(self.base_Dependency.client) |
| [2] SupplierIsNotGSNNode | -- supplier of InContextOf can be ContextualInformation or non-GSN concept, but it can not be GSNNode
ContextualInformation.allInstances().base_Element->includesAll(self.base_Dependency.supplier)
or
not GSNNode.allInstances().base_Element->includesAll(self.base_Dependency.supplier) |

SupportedBy

Package: GSN Profile

isAbstract: No

Extension: Dependency

Description

SupportedBy allows inferential or evidential relationships to be documented. Inferential relationships declare that there is an inference between goals in the argument. Evidential relationships declare the link between a goal and the evidence used to substantiate it. Permitted supported by connections are: goal-to-goal, goal-to-strategy, goal-to-solution, strategy to goal.




Figure 9.139 – SupportedBy

Constraints

- | | |
|--|---|
| [1] ClientIsGSNAArgumentNode | -- client of SupportedBy must be GSNAArgumentNode
GSNAArgumentNode.allInstances().base_Element->includesAll(self.base_Dependency.client) |
| [2] StrategyToGoal | -- if client is Strategy then supplier must be Goal
Strategy.allInstances().base_Class->includesAll(self.base_Dependency.client)
implies
Goal.allInstances().base_Class->includesAll(self.base_Dependency.supplier) |
| [3] SupplierIsNotContextualInformation | -- supplier of SupportedBy can be GSNNode or non-GSN concept, but it can not be ContextualInformation
GSNNode.allInstances().base_Element->includesAll(self.base_Dependency.supplier)
or
not ContextualInformation.allInstances().base_Element->includesAll(self.base_Dependency.supplier) |
| [4] ClientIsNotUndeveloped | -- client can not be Undeveloped Strategy nor Goal
-- if strategy or goal is client of SupportedBy - it is developed
not Undeveloped.allInstances().base_Element->includesAll(self.base_Dependency.client) |

9.8 Methods::ISO 26262

The ISO 26262 package contains elements supporting the analysis and requirement specification aspects of Functional Safety, as specified by ISO 26262 standard for automotive applications. ISO 26262 is a risk-based standard derived from IEC 61508. The ISO 26262 package redefines or extends concepts from the Core concepts package and the General Concepts package.

The ISO 26262 package enables modeling a HAZOP, which is typically used to identify malfunctioning behaviors. The failure modes concept is used from the General Concepts and specialized as a malfunctioning behavior. This allows the malfunctioning behavior to be related to the system behaviors through the HAZOP guidewords for construction of the HAZOP table. The risk analysis is performed by identifying Hazards that could result from the MalfunctioningBehavior, which in combination with a particular OperationalSituation could result in an AccidentScenario. This information is contained in the HazardousEvent which provides the risk level assessment for the event. Each of these concepts are modeled using elements defined in the ISO 26262 package as extensions of the Core and General concepts. This means that the same elements can be used in other analyses in the model, such as in an FMEA.

9.8.1 Methods::ISO 26262::ISO 26262 Library

TrafficAndPeople

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: [«OperationalSituation»](#)

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behaviour of any motorists or non-motorists considered in a hazardous event.




Figure 9.140 – TrafficAndPeople

VehicleUsage

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: [«OperationalSituation»](#)

Description

VehicleUsage extends the <<situation>> class and is used to describe the usage of a vehicle during a hazardous event.




Figure 9.141 – VehicleUsage

RoadCondition

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: «OperationalSituation»

Description

RoadConditions extends the <<situation>> class, and is used to describe the conditions or state of the surface a vehicle is driving on (Low-traction, Grade(Slope), etc.) during a hazardous event.




Figure 9.142 – RoadCondition

Location

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: «OperationalSituation»

Description

VehicleLocation extends the <<situation>> class and is used to describe the physical location (high speed road, intersection, parking lot, etc.) of a vehicle during a hazardous event.




Figure 9.143 – Location

EnvironmentalCondition

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: «OperationalSituation»

Description

EnvironmentalConditions extends the <<situation>> class and is used to describe the environmental conditions at the time of vehicle operation in a hazardous event.




Figure 9.144 – EnvironmentalCondition

OperationalCondition

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AbstractEvent](#)

Applied Stereotype: [«OperationalSituation»](#)

Description

Component/part of operational situation.




Figure 9.145 – OperationalCondition

AbstractOperationalSituation

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [OperationalCondition](#)

Applied Stereotype: [«OperationalSituation»](#)

Description

Operational situation is a scenario that can occur in vehicle's life.




Figure 9.146 – AbstractOperationalSituation

Attributes

conditions : OperationalCondition[*]
(member end of association)

Exposure : Exposure[1] , redefines
[likelihood](#)

Likelihood of being in a particular operational situation.
Must have a Rationale attached.

TypicalAutomotiveSituation

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AbstractOperationalSituation](#)

Applied Stereotype: [«OperationalSituation»](#)

Description

A grouping of operational conditions, including traffic and people, vehicle usage, road conditions, location, and environmental conditions.




Figure 9.147 – TypicalAutomotiveSituation

Attributes

trafficAndPeople : TrafficAndPeople[0..*]
(member end of association, subsets [conditions](#))

vehicleUsage : VehicleUsage[0..*]
(member end of association, subsets [conditions](#))

roadCondition : RoadCondition[0..*]
(member end of association, subsets [conditions](#))

location : Location[0..*] (member end of association, subsets [conditions](#))

environmentalCondition :
EnvironmentalCondition[0..*] (member end of association, subsets [conditions](#))

Exposure

Package: ISO 26262 Library

isAbstract: No

Applied Stereotype: «ValueType»

Description

Possible values of exposure.

«ValueType» Exposure
E0
E1
E2
E3
E4

Figure 9.148 – Exposure

Severity

Package: ISO 26262 Library

isAbstract: No

Applied Stereotype: «ValueType»

Description

Possible values for severity.

«ValueType» Severity
S0
S1
S2
S3

Figure 9.149 – Severity

ASIL

Package: ISO 26262 Library

isAbstract: No

Applied Stereotype: «ValueType»

Description

Possible ASIL values.

«valueType» ASIL
no assignment
QM
A
B
C
D
A(B)
A(C)
A(D)
B(C)
B(D)
C(D)
A(A)
B(B)
C(C)
D(D)
QM(A)
QM(B)
QM(C)
QM(D)

Figure 9.150 – ASIL

Controllability

Package: ISO 26262 Library

isAbstract: No

Applied Stereotype: «ValueType»

Description

Possible values of controllability.

«valueType» Controllability
C0
C1
C2
C3

Figure 9.151 – Controllability

Less

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from providing less output/behaviour than required.




Figure 9.152 – Less

More

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from providing more output/behaviour than required.




Figure 9.153 – More

No

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from the behaviour not being performed when required.




Figure 9.154 – No

Intermittent

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure from the behaviour being performed intermittently.




Figure 9.155 – Intermittent

Unintended

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from the behaviour being provided when not required.




Figure 9.156 – Unintended

Early

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from the behaviour being performed earlier than required.




Figure 9.157 – Early

Late

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from the behaviour being performed later than required.




Figure 9.158 – Late

Inverted

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AnyMalfunction](#)

Applied Stereotype: [«MalfunctioningBehavior»](#)

Description

A subclass of malfunctioning behaviour used for classification purposes. Must be connected to a behavioural element (Use Case or Function). This kind of malfunctioning behaviour represents a failure resulting from the behaviour providing an inverted output.




Figure 9.159 – Inverted

HazardousEvent

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AbstractRisk](#)

Applied Stereotype: «Situation»

Description

Combination of hazard and operational situation to identify automotive safety integrity level.




Figure 9.160 – HazardousEvent

Attributes

scenario : AccidentScenario[1] (member end of association, redefines [trigger](#))

hazard : Hazard[0..*] (member end of association, redefines [harmPotential](#))

systemLevelEffect : SystemLevelEffect[0..*] (member end of association)

vehicleLevelEffect : VehicleLevelEffect[0..*] (member end of association, redefines [harm](#))

ASIL : ASIL[0..*], redefines [score](#)

Automotive Safety Integrity Level value - one of four levels to specify necessary requirements for ISO-26262 and safety measures for avoiding unreasonable risks.

AnyMalfunction

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [UndesiredState](#)

Applied Stereotype: «MalfunctioningBehavior»

Description

Root of all malfunctioning behaviours.




Figure 9.161 – AnyMalfunction

AutomotiveEffect

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AbstractEffect](#)

Applied Stereotype: «Situation»

Description

System- or vehicle-level effect which is or could result in harm.




Figure 9.162 – AutomotiveEffect

Attributes

Severity : Severity[1], redefines [severity](#) Estimate of the extent of harm.
 Must have a Rationale attached.

ISO26262SafetyRequirementTemplate

Package: ISO 26262 Library

isAbstract: No

Applied Stereotype: «DependabilityRequirement»

Description

A template for dependability requirements.




Figure 9.163 – ISO26262SafetyRequirementTemplate

Attributes

ASIL : ASIL[1] ASIL value of the requirement.

FTTI : time[1] Fault Tolerant Time Interval.

AccidentScenario

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [DysfunctionalEvent](#), [Scenario](#)

Applied Stereotype: «Situation»

Description

A combination of operational situation and malfunctioning behaviour.




Figure 9.164 – AccidentScenario

Attributes

situation :
AbstractOperationalSituation[1..*]
(member end of association, subsets
[scenarioStep](#))

Controllability : Controllability[1] Ability to avoid a specified harm or damage through timely reactions of individuals involved in the scenario.
Must have a Rationale attached.

malfunctioningBehavior :
AnyMalfunction[1] (member end of
association, subsets [scenarioStep](#))

AnyTrafficAndPeople

Package: ISO 26262 Library

isAbstract: No

Generalization: [OperationalCondition](#), [TrafficAndPeople](#)

Applied Stereotype: «OperationalSituation»

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behaviour of any motorists or non-motorists considered in a hazardous event.



Figure 9.165 – AnyTrafficAndPeople

AnyVehicleUse

Package: ISO 26262 Library

isAbstract: No

Generalization: [OperationalCondition](#), [VehicleUsage](#)

Applied Stereotype: «OperationalSituation»

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behaviour of any motorists or non-motorists considered in a hazardous event.




Figure 9.166 – AnyVehicleUse

AnyRoadCondition

Package: ISO 26262 Library

isAbstract: No

Generalization: [OperationalCondition](#), [RoadCondition](#)

Applied Stereotype: «OperationalSituation»

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behaviour of any motorists or non-motorists considered in a hazardous event.




Figure 9.167 – AnyRoadCondition

AnyLocation

Package: ISO 26262 Library

isAbstract: No

Generalization: [Location](#), [OperationalCondition](#)

Applied Stereotype: «OperationalSituation»

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behavior of any motorists or non-motorists considered in a hazardous event.




Figure 9.168 – AnyLocation

AnyEnvironmentalCondition

Package: ISO 26262 Library

isAbstract: No

Generalization: [EnvironmentalCondition](#), [OperationalCondition](#)

Applied Stereotype: «OperationalSituation»

Description

TrafficAndPeople extends the <<situation>> class and is used to describe the presence and behaviour of any motorists or non-motorists considered in a hazardous event.




Figure 9.169 – AnyEnvironmentalCondition

SystemLevelEffect

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AutomotiveEffect](#)

Applied Stereotype: «Situation»

Description

System- or vehicle-level effect which is or could result in harm.




Figure 9.170 – SystemLevelEffect

VehicleLevelEffect

Package: ISO 26262 Library

isAbstract: Yes

Generalization: [AutomotiveEffect](#)

Applied Stereotype: «Situation»

Description

System- or vehicle-level effect which is or could result in harm.




Figure 9.171 – VehicleLevelEffect

Methods::ISO 26262::ISO 26262 Library::Diagrams by elements

9.8.2 Methods::ISO 26262::ISO 26262 Profile

OperationalSituation

Package: ISO 26262 Profile

isAbstract: No

Generalization: [Situation](#)

Extension: Class

Description

A situation describes the operational scenario or driving scenario which is considered in a hazardous event, as part of the Hazard Analysis and Risk Assessment process.




Figure 9.172 – OperationalSituation

MalfunctioningBehavior

Package: ISO 26262 Profile

isAbstract: No

Generalization: [FailureMode](#)

Extension: Class

Description

A malfunctioning behaviour describes a failure or unintended behaviour of an item with respect to its design intent. It is a subtype of failure mode.




Figure 9.173 – MalfunctioningBehavior

Methods::ISO 26262::ISO 26262 Profile::RequirementManagement

IndependenceRequirement

Package: RequirementManagement

isAbstract: No

Generalization: DeriveReq

Extension: Abstraction

Description

A relationship between requirement elements indicating that the child requirement specifies an independence criterion that needs to be satisfied in order for an ASIL decomposition to be valid. The decomposition between the parent requirement and 2 other children requirements.




Figure 9.174 – IndependenceRequirement

ASILDecompose

Package: RequirementManagement

isAbstract: No

Generalization: DeriveReq

Extension: Abstraction

Description

An ASIL decompose relation is used to connect two safety requirements for the purposes of performing ASIL decomposition. The target requirement (supplier) should be of a higher abstraction than the source (client). ASIL decompose relations shall be applied in pairs (e.g., a requirement cannot be the supplier of a single ASIL decompose relation).




Figure 9.175 – ASILDecompose

SafeState

Package: RequirementManagement

isAbstract: No

Extension: Dependency

Description

A state of function realized by one or more architectural components. May be composed of several subfunctions or called by other functions. Associated with safety specific behaviours, typically (but not necessarily) triggered by a failure mode.




Figure 9.176 – SafeState

UserInfoRequirement

Package: RequirementManagement

isAbstract: No

Generalization: Satisfy

Extension: Abstraction

Description

A UserInfoRequirement relationship is a dependency which links a State to a requirement. The arrow direction points from a state (client) to a FSR or TSR (supplier). Linked requirements specify information that must be presented to vehicle occupants when the vehicle enters a safe state.




Figure 9.177 – UserInfoRequirement

RecoveryRequirement

Package: RequirementManagement

isAbstract: No

Generalization: Satisfy

Extension: Abstraction

Description

A RecoveryRequirement relationship is a dependency between a safe state and requirement where the requirement indicates the criteria to recover from the safe state to another operational mode.




Figure 9.178 – RecoveryRequirement

OperatingMode

Package: RequirementManagement

isAbstract: No

Extension: Dependency

Description

A state of function realized by one or more architectural components. May be composed of several subfunctions or called by other functions. Associated with specific behaviours.




Figure 9.179 – OperatingMode

FunctionalSafetyRequirement

Package: RequirementManagement

isAbstract: No

Generalization: [DependabilityRequirement](#), Requirement

Extension: Class

Description

A functional safety requirement specifies an implementation independent safety behaviour, or an implementation independent safety measure, required for achievement of a safety goal from which it is derived.




Figure 9.180 – FunctionalSafetyRequirement

SoftwareSafetyRequirement

Package: RequirementManagement

isAbstract: No

Generalization: [DependabilityRequirement](#), Requirement

Extension: Class

Description

A software safety requirement provides implementation details for software. They can express behaviours or specific software mechanisms which realize the technical safety requirements from which they are derived.




Figure 9.181 – SoftwareSafetyRequirement

HardwareSafetyRequirement

Package: RequirementManagement

isAbstract: No

Generalization: [DependabilityRequirement](#), Requirement

Extension: Class

Description

A hardware safety requirement specifies hardware behaviours or hardware specific details necessary for implementing the safety concept. Hardware safety requirements are implementation specific and assigned to components or subcomponents.




Figure 9.182 – HardwareSafetyRequirement

TechnicalSafetyRequirement

Package: RequirementManagement

isAbstract: No

Generalization: [DependabilityRequirement](#), Requirement

Extension: Class

Description

A technical safety requirement specifies the implementation of the functional safety requirement(s) from which it is derived. Technical safety requirements express the behaviours and details necessary to realize the safety aspects of the item at the system level. Additional details that do not act at the system level can be specified in the hardware safety requirements or software safety requirements.




Figure 9.183 – TechnicalSafetyRequirement

SafetyGoal

Package: RequirementManagement

isAbstract: No

Generalization: [DependabilityRequirement](#), Requirement

Extension: Class

Description

A safety goal extends the SysML <<Requirement>> stereotype. It represents a top-level safety requirement, defined as a result of the Hazard Analysis and Risk Assessment process.




Figure 9.184 – SafetyGoal

DependabilityRequirement

Package: RequirementManagement

isAbstract: Yes

Generalization: AbstractRequirement, Block

Extension: Class

Description

Parent type of all subtypes of safety requirements




Figure 9.185 – DependabilityRequirement

Verified

Package: ISO 26262 Profile

isAbstract: No

Extension: Class

Description

Marker, indicating that hazardous event has been verified.




Figure 9.186 – Verified

Attributes

result : String[1]

Verification result

Confirmed

Package: ISO 26262 Profile

isAbstract: No

Extension: Class

Description

Marker, indicating that hazardous event has been confirmed.




Figure 9.187 – Confirmed

Attributes

result : String[1]

Confirmation result

HazardAndRiskAssessment

Package: ISO 26262 Profile

isAbstract: No

Extension: Package

Description

Grouping package for storing hazardous events.




Figure 9.188 – HazardAndRiskAssessment

LessonLearned

Package: ISO 26262 Profile

isAbstract: No

Extension: Comment

Description

Comments about lessons learned from hazard and risk assessment.




Figure 9.189 – LessonLearned

ASILAssignment

Package: ISO 26262 Profile

isAbstract: No

Extension: Element

Description

Stereotype for assigning ASIL values on system design elements.




Figure 9.190 – ASILAssignment

Attributes

ASIL : ASIL[1]

ASIOVERRIDE : ASIL[0..1]

The associated ASIL value of the system design element.

An ASIL value which does not follow from the normal ASIL derivation rules but is exceptional. This exceptional value needs to have an associated rationale.

ASIOVERRIDErationale

Package: ISO 26262 Profile

isAbstract: No

Generalization: Rationale

Extension: Comment

Description

A rationale specifically justifying ASIL Override value.




Figure 9.191 – ASIOVERRIDErationale

9.9 Methods::RBD

A Reliability Block Diagram (RBD) is a graphical representation used in reliability engineering to analyze the reliability and availability of complex systems. It is a method for assessing the performance of systems composed of multiple components, sub-systems, or processes. In an RBD, system elements (components or groups of components defined as an assemblies, subsystems, or other system architectural elements) are depicted as blocks, and these blocks are connected by lines to represent how they are interconnected or dependent on each other. The goal is to evaluate the overall reliability and availability of the entire system by considering the reliability characteristics of each component and their interconnections.

The method is based on IEC 61078:2016 ("Reliability block diagrams") includes the following concepts:

- Probability distributions, cumulative distribution functions (CDFs), probability density functions (PDFs), and hazard functions (the exponential, Weibull, and lognormal distributions are included in the library but the framework allows for additional distributions)
- Component reliability, failure probability, restoration completion probability, failure rate, restoration rate, mean time to failure, and mean time to restore
- Restorable and non-restorable systems
- System reliability and availability calculations for series, parallel, homogeneous k-out-n, and heterogeneous k-out-of-n systems

Mathematical methods for calculation of cumulative distributions functions (CDFs), probability density functions (PDFs), hazard functions, and mean values of distributions are based on U.S. National Institute of Standards Handbook of Engineering Statistics (see references).

9.9.1 Methods::RBD::RBD Library

AbstractReliabilitySituation

Package: RBD Library
isAbstract: Yes

Generalization: AnySituation

Applied Stereotype: «Situation»

Description

The parent situation of the RBD library. Specialization of AnySituation from Core Library.




Figure 1.192 - AbstractReliabilitySituation

Attributes

reliability : Real	Value property for reliability in AbstractReliabilitysituation (used to hold result of system or component reliability in non-restorable and restorable systems)
failureProbability : Real	Value property that is the complement of reliability
pcf : ProbabilityComplementFunction	Constraint property for calculating the complement of a value between 0 and 1

Restorable

Package: RBD Library
isAbstract: Yes

Generalization: AbstractReliabilitySituation

Applied Stereotype: «Situation»

Description

Specialization of AbstractReliabilitySituation for restorable systems. Parent of ResteorabailitySystemReliablitiySituation and RestorableComponentReliabilitySituationSituation. Also has composition relationship (owns) RestorableSystemReliabilitySituation to enable recursion




Figure 1.193 - Restorable
Attributes

availability : Real

Availability value property of Restorable

ComponentReliabilitySituation

Package: RBD Library

isAbstract: Yes

Generalization: AbstractReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for Components in RBDs. Specialization of AbstractReliabilitySituation and parent of RestorableComponentReliabilitySituation, NonrestorableComponentReliabilitySituations. Owns Reliability ParameterGroup constraint and failurerate, shape, scale, and location distribution parameters that it provides its children




Figure 1.194 - ComponentReliabilitySituation

Attributes

<u>failureRPD :</u> <u>ReliabilityParameterDistribution</u>	<u>Constraint property for expression of the reliability probability distribution</u>
<u>failureRate : Real</u>	<u>Value property for the failure rate</u>
<u>shape : Real</u>	<u>Value property for the shape parameter of the reliability probbability distribution</u>
<u>scale : Real</u>	<u>Value property for the scale parameter of the reliability probbability distribution</u>
<u>location : Real</u>	<u>Value property for the location parameter of the reliability probbability distribution</u>

RestorableComponentReliabilitySituation

Package: RBD Library

isAbstract: Yes

Generalization: ComponentReliabilitySituation, Restorable

Applied Stereotype: «Situation»

Description

Situation for restorable (repairable) component RBDs. Specialization of ComponentReliabilitySituation. Owns restorationRPG (Reliability Parameter Group) and RatioOfPartTotal (for determining availability). Value properties include MTBF, MTTR, restoration distribution parameters (shape, scale, and location), restorationCompletionProbability (calculated from restoration CDF) and restorationrate (calculated from restoration hazard function, i.e., ratio of PDF to CDF).




Figure 1.195 - RestorableComponentReliabilitySituation
Attributes

MTBF : time	Value property for Mean Time Between Failures (MTBF is used for restorable systems)
MTTR : time	Value property for Mean Time to Restoration
restorationRPD : ReliabilityParameterDistribution	Constraint property for restoration probability distribution
restoreCompletionProbability : Real	Value property for completion probability of restoration action (the value of the CDF for restoration at a specified time)
restoreNonCompletionProbability : Real	Value property for the complement of the restoration completion probability
restorationRate : Real	Value property for the ratio of the restoration pdf to the restoration CDF at a specified time
restorationShape : Real	Value property shape parameter of the restoration probability distribution

restorationScale : Real	Value property for the scale parameter of the restoration distribution
restorationLocation : Real	Value property for the location parameter of the restoration distribution (value of the location parameter must be less than the specified time)
availabilityCalc : RatioOfPartToTotal	Constraint property for the calculation of availability

NonRestorableComponentReliabilitySituation

Package: RBD Library
isAbstract: Yes

Generalization: ComponentReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for norestorable component RBDs. Specialization of ComponentReliabilitySituation. Owns MTTF value property




Figure 1.196 - NonRestorableComponentReliabilitySituation

Attributes

MTTF : time	Value property for the Mean Time to Failure (MTTF is used for non-restorable components or systems)
-------------	---

SystemReliabilitySituation

Package: RBD Library
isAbstract: Yes

Generalization: AbstractReliabilitySituation, Scenario

Applied Stereotype: «Situation»

Description

The parent situation for calculating a system reliability or availablity. Speciaalization of AbstractReliabilitySituation.




Figure 1.197 - SystemReliabilitySituation
Attributes

rb : AbstractReliabilitySituation[0..*]
(member end of association, redefines
scenarioStep)

Part property of SystemReliabilitySituation of type Restorable (see
Restorable situation)

RestorableSystemReliabilitySituation

Package: RBD Library
isAbstract: Yes

Generalization: Restorable, SystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for Resetable Systems. Specialization of SystemReliabilitySituation and part of Restorable Situation




Figure 1.198 - RestorableSystemReliabilitySituation
Attributes

rb : Restorable[0..*] (member end of association, redefines rb)

Part property of RestorableSystemReliabilitySituation of type Restorable (see Restorable situation)

InSeries

Package: RBD Library
isAbstract: Yes

Generalization: SystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of reliability or availability for series systems. Specialization of SystemReliabilitySituation. Owns InSeries constraint block.




Figure 1.199 - InSeries
Attributes

rc : InSeriesCalculation

Constraint property for series reliability calculation

RestorableInSeries

Package: RBD Library
isAbstract: Yes

Generalization: InSeries, RestorableSystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of availability for restorable series systems. Specialization of SystemReliabilitySituation and the InSeries situation. Owns InSeries constraint block.




Figure 1.200 - RestorableInSeries
Attributes

ac : InSeriesCalculation

Constraint property for availability

InParallel

Package: RBD Library
isAbstract: Yes

Generalization: SystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of reliability or availability for parallel systems. Specialization of SystemReliabilitySituation. Owns InParallel constraint block.




Figure 1.201 - InParallel

Attributes

rc : InParallelCalculation

Constraint property for availability

RestorableInParallel

Package: RBD Library

isAbstract: Yes

Generalization: InParallel, RestorableSystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of availability for restorable parallel systems. Specialization of RestorableSystemReliabilitySituation and InParallel situation. Owns InParallel constraint block.




Figure 1.202 - RestorableInParallel

Attributes

ac : InParallelCalculation

Constraint property for availability

HomogeneousKofN

Package: RBD Library

isAbstract: Yes

Generalization: SystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of reliability or availability for Homogeneous K out of N systems. Specialization of SystemReliabilitySituation. Owns HomogenousKofN constraint block.




Figure 1.203 - HomogeneousKofN

Attributes

rc : HomogeneousKofNCalculation

Constraint property for series reliability calculation

k : Integer

Value property for number of items needed for operation

n : Integer

Value property for Number of items installed or ready at start of operation

RestorableHomogeneousKofN

Package: RBD Library

isAbstract: Yes

Generalization: HomogeneousKofN, RestorableSystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of availability for Homogeneous K out of N systems. Specialization of RestorableSystemReliabilitySituation and the InSeries situation. Owns KofN constraint block.




Figure 1.204 - RestorableHomogeneousKofN

Attributes

ac : HomogeneousKofNCalculation

Constraint property for availability

HeterogeneousKofN

Package: RBD Library

isAbstract: Yes

Generalization: SystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of reliability or availability for Heterogeneous K out of N systems. Specialization of SystemReliabilitySituation. Owns HeterogeneousKofN constraint block.




Figure 1.205 - HeterogeneousKofN

Attributes

rc : HeterogeneousKofNCalculation

Constraint property for series reliability calculation

k : Integer

Number of items needed for operation

RestorableHeterogeneousKofN

Package: RBD Library

isAbstract: Yes

Generalization: HeterogeneousKofN, RestorableSystemReliabilitySituation

Applied Stereotype: «Situation»

Description

Situation for calculation of availability for Heterogeneous K out of N systems. Specialization of RestorableSystemReliabilitySituation and the InSeries situation. Owns HeterogeneousKofN constraint block.




Figure 1.206 - RestorableHeterogeneousKofN

Attributes

ac : HeterogeneousKofNCalculation

Constraint property for availability

9.9.2 Methods::RBD::RBD Library::ConstraintBlocks

9.9.2.1 Methods::RBD::RBD Library::ConstraintBlocks::Probability

OneVariableFunction

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This is an abstract constraint block which defines an input and an output for a constraint expression which has a single input and output




Figure 9.207 – OneVariableFunction

Attributes

x : Real

y : Real

The input parameter

The output parameter

ProbabilityComplementFunction

Package: Probability
isAbstract: No

Generalization: OneVariableFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the complemenet (i.e., 1 -) the input and is used for converting behind reliability and failure probability or between restoration completion success probability and restoration completion failure probability




Figure 9.208 – ProbabilityComplementFunction

Constraints

[1]

y=1.0-x

ReciprocalFunction

Package: Probability
isAbstract: No

Generalization: OneVariableFunction

Applied Stereotype: «ConstraintBlock»

Description

Provides the reciprocal of the input




Figure 9.209 – ReciprocalFunction

Constraints

[1] y=1.0/x

RatioOfPartToTotal

Package: Probability
isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

A constraint expression to calculate the proportion of one value to its sum (e.g., availability = MTBF/(MTBF+MTTR))




Figure 9.210 – RationOfPartToTotal

Attributes

x : Real	The numerator
y : Real	The other value
ratio : Real	=x/(x+y)

Constraints

[1] ratio = x/(x+y)

ProbabilityDensityFunction

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This is an abstract constraint block which defines 3 inputs (shape, scale, and location) and one output for a probability density function




Figure 9.211 – ProbabilityDensityFunction

Attributes

time : time

The specified operating (exposure) time

shape : Real

the shape parameter of a probability distribution (see NIST/Sematech Engineering Statistics Handbook, section 8.1.6)
<https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm>

scale : Real

the scale parameter of a probability distribution (see NIST/Sematech Engineering Statistics Handbook, section 8.1.6)
<https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm>

location : time

the location parameter of a probability distribution (see NIST/Sematech Engineering Statistics Handbook, section 8.1.6)
<https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm>

probabilityDensity : Real

The output parameter providing the value of the probability density function at the specified operating time

ExponentialProbabilityDensityFunction

Package: Probability

isAbstract: No

Generalization: ProbabilityDensityFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the cumulative distribution (CDF) for function for the exponential distribution.




Figure 9.212 – ExponentialProbabilityDensityFunction

Constraints

[1] $probabilityDensity = scale * Math.pow(Math.E, -1.0 * scale * (time - location))$

WeibullProbabilityDensityFunction

Package: Probability

isAbstract: No

Generalization: ProbabilityDensityFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the probability density function (PDF) for function for the Weibull distribution.




Figure 9.213 – WeibullProbabilityDensityFunction

Constraints

[1] $\text{probabilityDensity} = \text{Math.pow}(\text{Math.E}, -1.0 * \text{Math.pow}((\text{time}-\text{location})/\text{scale}, \text{shape}))$

LognormalProbabilityDensityFunction

Package: Probability

isAbstract: No

Generalization: ProbabilityDensityFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the probability density function (PDF) for function for the lognormal distribution.




Figure 9.214 – LognormalProbabilityDensityFunction

Constraints

[1] $\text{probabilityDensity} = \text{Math.pow}(\text{Math.E}, -1.0 * \text{Math.pow}((\text{time}-\text{location})/\text{scale}, \text{shape}))$

CumulativeDistributionFunction

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This abstract constraint block defines the parameters and is the parent of specific cumulative distribution constraint blocks (exponential, Weibull, lognormal, etc.). The parameters include the shape, scale, and location parameters of the distribution, the time at which the value is to be evaluated, and the resultant probability (an output result). This probability is defined for the reliability distribution. Note that the cumulative is for the reliability distribution, which is often the complement of the distribution used by other software tools (e.g., Excel or R).




Figure 9.215 – CumulativeDistributionFunction

Attributes

<u>time : time</u>	<u>The time at which the CDF is evaluated. If a location parameter is used, then the value of time must be greater than the value of the location parameter</u>
<u>shape : Real</u>	<u>The shape parameter for the CDF</u>
<u>scale : Real</u>	<u>The scale parameter for the CDF</u>
<u>location : Real</u>	<u>The location parameter (in units of time) for the CDF</u>
<u>probability : Real</u>	<u>The output probability calculated by the CDF</u>

ExponentialCumulativeDistributionFunction

Package: Probability

isAbstract: No

Generalization: CumulativeDistributionFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the cumulative distribution (CDF) for function for the exponential distribution. See Cumulative Distribution Function constraint block note explaining how the CDF is defined.




Figure 9.216 – ExponentialCumulativeDistributionFunction

Constraints

[1] $\text{probability} = \text{Math.pow}(\text{Math.E}, -1.0 * \text{scale} * (\text{time} - \text{location}))$

WeibullCumulativeDistributionFunction

Package: Probability

isAbstract: No

Generalization: CumulativeDistributionFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the cumulative distribution (CDF) for function for the Weibull distribution. See Cumulative Distribution Function constraint block note explaining how the CDF is defined.




Figure 9.217 – WeibullCumulativeDistributionFunction

Constraints

[1] $\text{probability} = \text{Math.pow}(\text{Math.E}, -1.0 * \text{Math.pow}((\text{time} - \text{location}) / \text{scale}, \text{shape}))$

LognormalCumulativeDistributionFunction

Package: Probability

isAbstract: No

Generalization: CumulativeDistributionFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the cumulative distribution (CDF) for function for the lognormal distribution. See Cumulative Distribution Function constraint block note explaining how the CDF is defined.




Figure 9.218 – LognormalCumulativeDistributionFunction

Constraints

[1] $probability = \text{Math.pow}(\text{Math.E}, -1.0 * \text{Math.pow}((\text{time}-\text{location})/\text{scale}, \text{shape}))$

MeanFunction

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This abstract constraint block defines the input and output parameters for calculating the mean and is the parent of specific cumulative distribution constraint blocks (exponential, Weibull, lognormal, etc.). The parameters include the shape, scale, and location parameters of the distribution, the time at which the value is to be evaluated, and the resultant probability (an output result). The mean is defined for the reliability distribution.




Figure 9.219 – MeanFunction

Attributes

time : time The time at which the mean function is evaluated. If a location parameter is used, then the value of time must be greater than the value of the location parameter

shape : Real	The shape parameter for the probabiltiy distribution for which the mean is being calculated
scale : Real	The scale parameter of the probabiltiy distribution function for which the mean is being calculated
location : Real	The location parameer of the probabiltiy distribution function for which the mean is being calculated
meanTimeToEvent : time	The output of the mean function

ExponentialMeanFunction

Package: Probability
isAbstract: No
Generalization: MeanFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the mean of the exponential function (i.e., MTBF or MTTR). Note that for the exponential function, the mean is equiavlent to the reciprocal of the hazard function.




Figure 9.220 – ExponentialMeanFunction

Constraints

- [1] meanTimeToEvent = 1.0/scale

WeibullMeanFunction

Package: Probability
isAbstract: No
Generalization: MeanFunction
Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the mean of the Weibull distribution (i.e., MTBF or MTTR). Note that for the exponential function, the mean is equivalent to the reciprocal of the hazard function.




Figure 9.221 – WeibullMeanFunction

Constraints

[1] meanTimeToEvent = Math.pow(Math.E, -1.0 * Math.pow((time-location)/scale, shape))

LognormalMeanFunction

Package: Probability
isAbstract: No

Generalization: MeanFunction

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates the mean of the lognormal function (i.e., MTBF or MTTR). Note that for the exponential function, the mean is equivalent to the reciprocal of the hazard function.




Figure 9.222 – LognormalMeanFunction

Constraints

[1] `meanTimeToEvent = Math.pow(Math.E, -1.0 * Math.pow((time-location)/scale, shape))`

HazardFunction

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This abstract constraint block defines the parameters used in the hazard function. The hazard function is the ratio of the probability density function and the cumulative distribution function




Figure 9.223 – HazardFunction

Attributes

<u>time : time</u>	The time at which the hazard function is being evaluated
<u>shape : Real</u>	The shape parameter for the hazard for which the hazard is being calculated
<u>scale : Real</u>	The scale parameter for the hazard function for which the sis being calculated

location : Real

The location parameter for the hazard function for which the sis being calculated

eventRate : Real

The output of the hazard distribution function

ExponentialHazardFunction

Package: Probability

isAbstract: No

Generalization: HazardFunction, MeanFunction

Applied Stereotype: «ConstraintBlock»

Description

This is the constraint block is a specialization of the hazard function constraint block and calculates the hazard function (failure rate) for the exponential distribution. Note that for the exponential distribution, the hazard function is a constant over time.




Figure 9.224 – ExponentialHazardFunction

Constraints

[1]eventRate = scale

WeibullHazardFunction

Package: Probability

isAbstract: No

Generalization: HazardFunction, MeanFunction

Applied Stereotype: «ConstraintBlock»

Description

This is the constraint block is a specialization of the hazard function constraint block and calculates the hazard function (failure rate) for the Weibull distribution. . .




Figure 9.225 – WeibullHazardFunction

Constraints

[1] $\text{eventRate} = \text{Math.pow}(\text{Math.E}, -1.0 * \text{Math.pow}((\text{time}-\text{location})/\text{scale}, \text{shape}))$

LognormalHazardFunction

Package: Probability

isAbstract: No

Generalization: HazardFunction, MeanFunction

Applied Stereotype: «ConstraintBlock»

Description

This is the constraint block is a specialization of the hazard function constraint block and calculates the hazard function (failure rate) for the lognormal distribution. .




Figure 9.226 – LognormalHazardFunction

Constraints

[1] `eventRate = Math.pow(Math.E, -1.0 * Math.pow((time-location)/scale, shape))`

ReliabilityParameterDistribution

Package: Probability

isAbstract: Yes

Applied Stereotype: «ConstraintBlock»

Description

This constraint block is the parent of probability distributions and parameters. It owns the pdf, cdf, mean, hazard function, and complement constraint blocks. The parameters inherited by the children distributions include shape, scale, location, the instantaneous probability density value, probability value, complement value (e.g., failure probability from reliability), mean time to event (e.g., mean time between failures or mean time to failure), and event rate (e.g., failure rate). It also includes a time parameter which is the argument for the other parameters




Figure 9.227 – ReliabilityParameterDistribution

Attributes

<code>time : time</code>	The time at which the probability function is to be evaluated. Time must be greater than the location value
<code>shape : Real</code>	The shape parameter of the distribution
<code>scale : Real</code>	The scale parameter of the distribution
<code>location : Real</code>	The location parameter of the distribution
<code>probabilityDensity : Real</code>	The value of the probability density function at a specified time
<code>probability : Real</code>	The probability (i.e., value of the CDF) at a specified time
<code>pdf : ProbabilityDensityFunction</code>	The constraint expression of the probability density function
<code>cdf : CumulativeDistributionFunction</code>	The constraint expression for the cumulative density function
<code>mean : MeanFunction</code>	The constraint expression for the mean of the CDF
<code>hazardFunction : HazardFunction</code>	The constraint expression for the hazard function (ratio of PDF to CDF)

<u>complement :</u> <u>ProbabilityComplementFunction</u>	<u>A general expression to take the complement (i.e., 1-value).</u>
<u>probabilityComplement : Real</u>	<u>A general expression to take the complement of the probability (i.e., 1-value). The value for which the complement is calculated must be less than 1</u>
<u>meanTimeToEvent : time</u>	<u>The constraint expression to calculate the mean of the probability distribution</u>
<u>eventRate : Real</u>	<u>The constraint expression for determining the event rate (e.g., failure rate or repair rate) of the probability distribution</u>

ExponentialDistribution

Package: Probability
isAbstract: No
Generalization: ReliabilityParameterDistribution
Applied Stereotype: «ConstraintBlock»

Description
 This constraint block calculates owns 4 lower level constraint blocks for calculating the values of the cumulative, density, and hazard functions, as well as the mean for the exponential distribution. Note that for the exponential distribution function, only scale and location parameters are defined




Figure 9.228 – ExponentialDistribution

Attributes

pdf :	The PDF for the exponential distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
ExponentialProbabilityDensityFunction, redefines pdf	
cdf :	The CDF for the exponential distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
ExponentialCumulativeDistributionFunction, redefines cdf	
mean : ExponentialMeanFunction, redefines mean	The mean for the exponential distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
hazardFunction :	The hazard function for the exponential distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
ExponentialHazardFunction, redefines hazardFunction	

WeibullDistribution

Package: Probability

isAbstract: No

Generalization: ReliabilityParameterDistribution

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates owns 4 lower level constraint blocks for calculating the values of the cumulative, density, and hazard functions, as well as the mean for the Weibull distribution.




Figure 9.229 – WeibullDistribution

Attributes

<u>pdf</u> : WeibullProbabilityDensityFunction, redefines pdf	The PDF for the Weibull distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
<u>cdf</u> : WeibullCumulativeDistributionFunction, redefines cdf	The PDF for the Weibull distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
<u>mean</u> : WeibullMeanFunction, redefines mean	The mean for the Weibull distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
<u>hazardFunction</u> : WeibullHazardFunction, redefines hazardFunction	The hazard function for the Weibull distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6, https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm

LognormalDistribution

Package: Probability

isAbstract: No

Generalization: ReliabilityParameterDistribution

Applied Stereotype: «ConstraintBlock»

Description

This constraint block calculates owns 4 lower level constraint blocks for calculating the values of the cumulative, density, and hazard functions, as well as the mean for the lognormal distribution.




Figure 9.230 – LognormalDistribution

Attributes

pdf :	The PDF for the lognormal distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6.
LognormalProbabilityDensityFunction, redefines pdf	https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
cdf :	The CDF for the lognormal distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6.
LognormalCumulativeDistributionFunction, redefines cdf	https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
mean : LognormalMeanFunction, redefines mean	The mean for the lognormal distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6.
	https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm
hazardFunction :	The hazard function for the lognormal distribution defined in the NIST/Sematech Engineering Statistics Handbook, section 8.1.6.
LognormalHazardFunction, redefines hazardFunction	https://www.itl.nist.gov/div898/handbook/apr/section1/apr16.htm

9.9.2.2 Methods::RBD::RBD Library::ConstraintBlocks::SystemBlocks

InSeriesCalculation

Package: SystemBlocks
isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Constraint block for calculation of series system reliability or availability




Figure 9.231 – InseriesCalculation

Attributes

<code>input : Real[0..*]</code>	Probabilities (reliability or availability) of input components
<code>output : Real</code>	Series system reliability or availability

Constraints

[1]	<pre>if (input && !input.isEmpty()) { output = 1.0; } for (var i = input.iterator(); i.hasNext();) { output = i.next() * output; }</pre>
-----	--

InParallelCalculation

Package: SystemBlocks
isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Constraint block for calculation of parallel system reliability or availability




Figure 9.232 – InparallelCalculation

Attributes

input : Real[0..*]

Reliability or availability of components

output : Real[1]

Reliability or availability of system

Constraints

[1]

```

if (input && !input.isEmpty()) {
    output = 1.0;
}
for (var i = input.iterator(); i.hasNext(); ) {
    output = (1.0 - i.next()) * output;
}

output = 1.0 - output;
  
```

HomogeneousKofNCalculation

Package: SystemBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Constraint block for calculation of k out of n system reliability or availability




Figure 9.233 – HomogeneousKofNCalculation

Attributes

input : Real [1]

Reliability or availability of components (all components must have equal reliability or availability)

output : Real [1]

k ou tof n system reliability or availability

k : Integer [1]

Number of components or channels needed for system ro operate

n : Integer [1]

Number of components installed in system

Constraints

[1]

```

function factorial (n) {
  if (n < 2)
    return 1;
  return factorial(n-1)*n;
}

function C_k_of_n (k, n) {
  return (factorial(n)/factorial(k))/factorial(n-k);
}

var R = input;
var result = 0.0;
for (var i = k; i <= n; ++i) {
  result += C_k_of_n(i, n) * Math.pow(R, i) * Math.pow(1.0-R, n-i);
}

output = result;
  
```

HeterogeneousKofNCalculation

Package: SystemBlocks

isAbstract: No

Applied Stereotype: «ConstraintBlock»

Description

Constraint block for calculation of k out of n system reliability or availability where components have different reliabilities or availabilities




Figure 9.234 – HeterogeneousKofNCalculation

Attributes

input : Real[0..*]

Reliability or availability of components (components do not necessarily have equal reliability or availability)

output : Real[1]

Reliability or availability of system

k : Integer[1]

Number of components or channels needed for system to operate

Constraints

[1]

```
function getCombinations(array, min) {
  var res = [];
  function iter(i, temp, count) {
    if (i === array.length) {
      if (count >= min) {
        res.push(temp);
      }
      return;
    }
    iter(i + 1, temp.concat(array[i]), count + 1);
    iter(i + 1, temp.concat(1.0 - array[i]), count);
  }

  iter(0, [], 0);
  return res;
}

function and(arrayOfProbabilities) {
  var output = 1.0;
  for (i = 0; i < arrayOfProbabilities.length; i++) {
    output = arrayOfProbabilities[i] * output;
  }
  return output;
}

function sum(arrayOfProbabilities) {
  var output = 0.0;
  for (i = 0; i < arrayOfProbabilities.length; i++) {
    output = output + arrayOfProbabilities[i];
  }
  return output;
}

var allCombinations = getCombinations(input.toArray(), k);
var andsArray = [];
```

```
for (j = 0; j < allCombinations.length; j++) {  
  andsArray.push(and(allCombinations[j]));  
}  
  
output = sum(andsArray);
```

9.9.3 Methods::RBD::RBD Profile

ReliabilitySituation

Package: RBD Profile
isAbstract: Yes
Generalization: Situation
Extension: Class

Description
A marker stereotype for all reliability situations. See AbstractReliabilitySituation library class for definition.




Figure 9.235 – ReliabilitySituation

Restorable

Package: RBD Profile
isAbstract: No
Extension: Class

Description
A mixin stereotype for all restorable reliability situations - both component and system. See Restorable library class for definition.




Figure 9.236 – Restorable

Constraints

[1] RestorableIsRestorable self.base_Class->asSet()->closure(general).name->includes('Restorable')

ComponentReliability

Package: RBD Profile

isAbstract: No

Generalization: ReliabilitySituation

Extension: Class

Description

A marker stereotype for non-composite reliability situations. See ComponentReliabilitySituation library class for definition.




Figure 9.237 –ReliabilitySituation

Constraints

[1] ComponentReliabilityIsComponentReliabilitySituation self.base_Class->asSet()->closure(general).name->includes('ComponentReliabilitySituation')

SystemReliability

Package: RBD Profile

isAbstract: Yes

Generalization: ReliabilitySituation

Extension: Class

Description

A marker stereotype for composite reliability situations. See SystemReliabilitySituation library class for definition.




Figure 9.238 –SystemReliability

InSeries

Package: RBD Profile

isAbstract: No

Generalization: SystemReliability

Extension: Class

Description

A marker stereotype for in-series composite reliability situations. See InSeries library class for definition.




Figure 9.239 – InSeries

Constraints

[1] InSeriesIsInSeries `self.base_Class->asSet()->closure(general).name->includes('InSeries')`

InParallel

Package: RBD Profile

isAbstract: No

Generalization: SystemReliability

Extension: Class

Description

A marker stereotype for in-parallel composite reliability situations. See InParallel library class for definition.




Figure 9.240 – InParallel

Constraints

[1] InParallelIsInParallel `self.base_Class->asSet()->closure(general).name->includes('InParallel')`

HomogeneousKofN

Package: RBD Profile

isAbstract: No

Generalization: SystemReliability

Extension: Class

Description

A marker stereotype for homogeneous k-of-n composite reliability situations. See HomogeneousKofN library class for definition.




Figure 9.241 – HomogeneousKofN

Constraints

[1] self.base Class->asSet()->closure(general).name->includes('HomogeneousKofN')

HeterogeneousKofN

Package: RBD Profile

isAbstract: No

Generalization: SystemReliability

Extension: Class

Description

A marker stereotype for heterogeneous k-of-n composite reliability situations. See HeterogeneousKofN library class for definition.




Figure 9.242 – HeterogeneousKofN

Constraints

[11] self.base_Class->asSet()->closure(general).name-
HeterogeneousKofNIsHeterogeneousKofN >includes('HeterogeneousKofN')

Commented [AA76]: RAAML11-17

Formatted: English (United States)

Formatted: Body Text

10. Views

10.1 Core

10.1.1 Core::Core Library

View Core::Core Library::Core Library



Figure 10.1 – Core Library

Elements

- [AnySituation](#)
- [Causality](#)

10.1.2 Core::Core Profile

View Core::Core Profile::CoreProfile




Figure 10.2 – CoreProfile

Elements

- [ControllingMeasure](#)
- [RelevantTo](#)
- [Situation](#)
- [Violates](#)

10.2 General

10.2.1 General::General Concepts Library

View General::General Concepts Library::General Concepts Library




Figure 10.3 - General Concepts Library

Elements

- [AbstractCause](#)
- [AbstractEffect](#)
- [AbstractEvent](#)
- [AbstractFailureMode](#)
- [AbstractRisk](#)
- [Activation](#)
- [AnySituation](#)
- [Causality](#)
- [Cause](#)
- [DysfunctionalEvent](#)
- [Effect](#)
- [ErrorPropagation](#)
- [ErrorRealization](#)
- [FailureMode](#)
- [HarmPotential](#)
- [Hazard](#)
- [Scenario](#)
- [UndesiredState](#)

10.2.2 General::General Concepts Profile

View General::General Concepts Profile::General Concepts Profile




Figure 10.4 – General Concepts Profile

- Elements
- [ControllingMeasure](#)
 - [Detection](#)
 - [Error](#)
 - [FailureMode](#)
 - [FailureState](#)
 - [Fault](#)
 - [Mitigation](#)
 - [Prevention](#)
 - [Recommendation](#)
 - [Situation](#)
 - [Undeveloped](#)

10.3 General Security

10.3.1 General Security::General Security Concepts Library

View General Security::General Security Concepts Library::General Security Concepts Library




Figure 10.5 – General Security Concepts Library

- Elements
- [AbstractRisk](#)
 - [AnySituation](#)
 - [Causality](#)
 - [Factor](#)

Formatted: Font: 9.5 pt, No underline, Font color: Auto

Formatted: Outline numbered + Level: 3 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Font: (Default) Arial, 9 pt

Formatted: Font: 9 pt

Formatted: Default Paragraph Font, Font: (Default) Arial

Formatted: Default Paragraph Font, Font: (Default) Arial, Bold, Not Italic

- HarmPotential
- Hazard
- Limitation
- Scenario
- Threat
- Vulnerability
- Weakness

10.3.2 General Security::General Security Concepts Profile

View General Security::General Security Concepts Profile::General Security Concepts Profile




Figure 10.6 :- General Security Concepts Profile Elements

- Asset
- Hazard
- Impacts
- PresentedBy
- RelevantTo
- SecurityActor
- Situation
- Threat
- Valuates

Formatted: Outline numbered + Level: 3 + Numbering
Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at:
0" + Indent at: 0.25"

Formatted: Font: (Default) Arial, 9 pt
Formatted: Font: 9 pt
Formatted: Default Paragraph Font, Font: (Default) Arial
Formatted: Default Paragraph Font, Font: (Default) Arial,
Bold, Not Italic

Commented [AA77]: RAAML11-28

Formatted: No bullets or numbering

10.4 Methods::FMEA

10.4.1 Methods::FMEA::FMEA Library

View Methods::FMEA::FMEA Library::FMEA Library




Figure 10.7 – FMEA Library

Elements

- [AbstractCause](#)
- [AbstractEffect](#)
- [AbstractFailureMode](#)
- [AbstractFMEAItem](#)
- [AbstractRisk](#)
- [Cause](#)
- [DegradationOfFunction](#)

- [DelayedFunction](#)
- [Effect](#)
- [ExceedingFunction](#)
- [FailureMode](#)
- [FMEAItem](#)
- [IntermittentFunction](#)
- [LossOfFunction](#)
- [PartialFunction](#)
- [UnintendedFunction](#)

10.4.2 Methods::FMEA::FMEA Profile

View Methods::FMEA::FMEA Profile::FMEA Profile




Figure 10.8 – FMEA Profile

Elements

- [FMEAItem](#)

10.5 Methods::FTA

10.5.1 Methods::FTA::FTALibrary

Methods::FTA::FTALibrary::Events

View Methods::FTA::FTALibrary::Events::Events




Figure 10.9 – Events

Elements

- [BasicEvent](#)
- [ConditionalEvent](#)
- [DormantEvent](#)
- [Event](#)
- [HouseEvent](#)
- [IntermediateEvent](#)
- [TopEvent](#)
- [UndevelopedEvent](#)
- [ZeroEvent](#)

View Methods::FTA::FTALibrary::FTA Library




Figure 10.10 – FTA Library

Elements

- [AbstractEvent](#)
- [AND](#)
- [AnySituation](#)
- [Causality](#)
- [DysfunctionalEvent](#)
- [Event](#)
- [FTAElement](#)

- [FTATree](#)
- [Gate](#)
- [INHIBIT](#)
- [MAJORITY_VOTE](#)
- [NOT](#)
- [OR](#)
- [Scenario](#)
- [SEQ](#)
- [XOR](#)

10.5.2 Methods::FTA::FTAProfile

Methods::FTA::FTAProfile::Diagrams by elements

View Methods::FTA::FTAProfile::FTA Profile




Figure 10.11 – FTA Profile

Elements


- [AND](#)
- [BasicEvent](#)
- [ConditionalEvent](#)
- [DormantEvent](#)
- [Event](#)
- [Gate](#)
- [HouseEvent](#)
- [INHIBIT](#)
- [IntermediateEvent](#)

- [MAJORITY_VOTE](#)
- [NOT](#)
- [OR](#)
- [SEQ](#)
- [Situation](#)
- [TopEvent](#)
- [TransferIn](#)
- [TransferOut](#)
- [Tree](#)
- [Undeveloped](#)
- [XOR](#)
- [ZeroEvent](#)


10.6 Methods::STPA

10.6.1 Methods::STPA::STPA Library

View Methods::STPA::STPA Library::STPA Library



Commented [AA78]: RAAML11-28



Deleted:


Figure 10.12 – STPA Library

Elements

- [AbstractCause](#)
- [AbstractEffect](#)
- [AbstractEvent](#)
- [AbstractOperationalSituation](#)
- [AbstractRisk](#)
- [AnySituation](#)
- [Causality](#)
- [Early](#)
- [Factor](#)
- [HarmPotential](#)
- [Hazard](#)
- [Inadequate Control Execution](#)
- [Inadequate Controller Decisions](#)
- [Inadequate Feedback and Inputs](#)
- [Inadequate Process Behavior](#)
- [Late](#)
- [Limitation](#)
- [Loss](#)
- [LossScenario](#)
- [NotProvided](#)
- [OperationalCondition](#)
- [OutOfSequence](#)
- [ProcessModelFlaw](#)
- [ProcessModelFlawConsequence](#)
- [ProcessModelFlawFactor](#)
- [Provided](#)
- [RiskRealization](#)
- [Scenario](#)
- [Threat](#)
- [TooLong](#)
- [TooShort](#)
- [UndesiredState](#)
- [UndesiredControlAction](#)
- [UndesiredControlActionHarmPotential](#)
- [Vulnerability](#)
- [Weakness](#)

10.6.2 Methods::STPA::STPA Profile

View Methods::STPA::STPA Profile::STPA Profile






Figure 10.13 – STPA Profile

Elements

- [Actuator](#)
- [ControlAction](#)
- [ControlledProcess](#)
- [Controller](#)
- [ControlStructure](#)
- [FailureMode](#)
- [Feedback](#)
- [Sensor](#)
- [UndesiredControlAction](#)
- [UnsafeControlAction](#)

Commented [AA81]: RAAML11-28

Commented [AA82]: RAAML11-28

Deleted: [UnsafeControlAction](#)

Formatted: No underline, Font color: Auto

Commented [AA83]: RAAML11-28

10.7 GSN

10.7.1 GSN::GSN Profile

View GSN::GSN Profile::GSN Profile




Figure 10.14 – GSN Profile

Elements

- [Assumption](#)
- [Context](#)
- [Goal](#)
- [GSNArgumentNode](#)
- [GSNNode](#)
- [InContextOf](#)
- [Justification](#)
- [Solution](#)
- [Strategy](#)
- [SupportedBy](#)
- [ContextualInformation](#)
- [Undeveloped](#)

10.8.1 Methods::ISO 26262::ISO 26262 Library


View [Methods::ISO 26262::ISO 26262 Library::ISO26262 Library](#)

Figure 10.15 – ISO 26262 Library

Elements

- [AbstractEffect](#)
- [AbstractEvent](#)
- [AbstractOperationalSituation](#)
- [AbstractRisk](#)
- [AccidentScenario](#)
- [AnyMalfunction](#)
- [AnySituation](#)
- [ASIL](#)
- [AutomotiveEffect](#)
- [Causality](#)
- [Controllability](#)
- [DysfunctionalEvent](#)
- [Early](#)
- [EnvironmentalCondition](#)
- [Exposure](#)
- [HarmPotential](#)
- [Hazard](#)
- [HazardousEvent](#)
- [Intermittent](#)

- [Inverted](#)
- [ISO26262SafetyRequirementTemplate](#)
- [Late](#)
- [Less](#)
- [Location](#)
- [More](#)
- [No](#)
- [OperationalCondition](#)
- [RoadCondition](#)
- [Scenario](#)
- [Severity](#)
- [SystemLevelEffect](#)
- [TrafficAndPeople](#)
- [TypicalAutomotiveSituation](#)
- [UndesiredState](#)
- [Unintended](#)
- [VehicleLevelEffect](#)
- [VehicleUsage](#)

View Methods::ISO 26262::ISO 26262 Library::All-Encompassing Operational Situations




Figure 10.16 – All-Encompassing Operational Situations

Elements

- [AnyEnvironmentalCondition](#)
- [AnyLocation](#)
- [AnyRoadCondition](#)
- [AnyTrafficAndPeople](#)
- [AnyVehicleUse](#)
- [EnvironmentalCondition](#)
- [Location](#)
- [RoadCondition](#)
- [TrafficAndPeople](#)
- [VehicleUsage](#)

10.8.2 Methods::ISO 26262::ISO 26262 Profile

Methods::ISO 26262::ISO 26262 Profile::RequirementManagement

View Methods::ISO 26262::ISO 26262 Profile::RequirementManagement::RequirementManagement




Figure 10.17 – RequirementManagement

Elements

- [ASILDecompose](#)
- [DependabilityRequirement](#)
- [FunctionalSafetyRequirement](#)
- [HardwareSafetyRequirement](#)
- [IndependenceRequirement](#)
- [OperatingMode](#)
- [RecoveryRequirement](#)
- [SafeState](#)
- [SafetyGoal](#)
- [SoftwareSafetyRequirement](#)
- [TechnicalSafetyRequirement](#)
- [UserInfoRequirement](#)

View Methods::ISO 26262::ISO 26262 Profile::ISO26262 Profile




Figure 10.18 – ISO 26262 Profile

Elements

- [ASILAssignment](#)
- [ASILOverrideRationale](#)
- [Confirmed](#)
- [ControllingMeasure](#)
- [FailureMode](#)
- [HazardAndRiskAssessment](#)
- [IDCarrier](#)
- [LessonLearned](#)
- [MalfunctioningBehavior](#)
- [Mitigation](#)
- [OperationalSituation](#)
- [Situation](#)
- [Verified](#)

Deleted: <#>Silly stuff¶

Formatted: Font: 9.5 pt, No underline, Font color: Auto

10.9 Methods::RBD

10.9.1 Methods::RBD::RBD Library

[View Methods::RBD::RBD Library::RBD Library](#)



Figure 0.20 - AbstractReliabilitySituation

View Methods::RBD::RBD

Library::ComponentReliabilitySituation::ComponentReliabilitySituation




Figure 0.21 - ComponentReliabilitySituation

View Methods::RBD::RBD

Library::NonRestorableComponentReliabilitySituation::NonRestorableComponentReliabilitySituation




Figure 0.22 - InSeries

View Methods::RBD::RBD Library::RestorableInSeries::RestorableInSeries




Figure 0.23 - RestorableInSeries

View Methods::RBD::RBD Library::InParallel::InParallel




Figure 0.24 - InParallel

View Methods::RBD::RBD Library::RestorableInParallel::RestorableInParallel




Figure 0.25 - RestorableInParallel

View Methods::RBD::RBD Library::HomogeneousKofN::HomogeneousKofN




Figure 0.26 - HomogeneousKofN

View Methods::RBD::RBD

Library::RestorableHomogeneousKofN::RestorableHomogeneousKofN




Figure 0.27 - RestorableHomogeneousKofN

View Methods::RBD::RBD Library::HeterogeneousKofN::HeterogeneousKofN




Figure 0.28 - HeterogeneousKofN

View Methods::RBD::RBD

Library::RestorableHeterogeneousKofN::RestorableHeterogeneousKofN




Figure 0.29 - RestorableHeterogeneousKofN

10.9.2 Methods::RBD::RBD Library::ConstraintBlocks

10.9.2.1 Methods::RBD::RBD Library::ConstraintBlocks::Probability

View Methods::RBD::RBD Library::ConstraintBlocks::Probability::Distributions




Figure 0.30 - Distributions

Elements

- [ExponentialDistribution](#)
- [LognormalDistribution](#)
- [ReliabilityParameterDistribution](#)
- [WeibullDistribution](#)

View Methods::RBD::RBD Library::ConstraintBlocks::Probability::ReliabilityParameterDistribution::ReliabilityParameterDistribution




Figure 0.31 - ReliabilityParameterDistribution

10.9.3 Methods::RBD::RBD Profile

View Methods::RBD::RBD Profile::RBD Profile




Figure 0.32 - RBD Profile

Elements

- [ComponentReliability](#)

- [HeterogeneousKofN](#)
- [HomogeneousKofN](#)
- [InParallel](#)
- [InSeries](#)
- [ReliabilitySituation](#)
- [Restorable](#)
- [Situation](#)
- [SystemReliability](#)




Figure 0.33 - NonRestorableComponentReliabilitySituation

View Methods::RBD::RBD

Library::RestorableComponentReliabilitySituation::RestorableComponentReliabilitySituation




Figure 0.34 - RestorableComponentReliabilitySituation

Commented [AA84]: RAAML11-17

Formatted: No bullets or numbering